# **Product datasheet**





## molded case switch-disconnector Compact NS1250 NA - 1250 A - 4 poles

33427

! Discontinued on: 31 Mar 2024

! To be discontinued

#### Main

Product Name	ComPact NS	
Device Short Name	Compact NS1250 NA	
Product Or Component Type	Switch disconnector	
Device Application	Distribution	
Offer Type	C4	
Poles Description	4P	
Network Type	AC	
Performance Level	NA	
Suitability For Isolation	Yes conforming to IEC 60947-3	

## Complementary

Network Frequency	50/60 Hz	
Control Type	Toggle	
Mounting Mode	Fixed	
Mounting Support	Chassis	
[le] Rated Operational Current	AC-23A: 1250 A AC 50/60 Hz 220/240 V AC-23A: 1250 A AC 50/60 Hz 380/415 V AC-23A: 1250 A AC 50/60 Hz 440/480 V AC-23A: 1250 A AC 50/60 Hz 500/525 V AC-23A: 1250 A AC 50/60 Hz 660/690 V	
[Ui] Rated Insulation Voltage	800 V AC 50/60 Hz conforming to IEC 60947-3	
[Uimp] Rated Impulse Withstand Voltage	8 kV conforming to IEC 60947-3	
[Ith] Conventional Free Air Thermal Current	1250 A at 60 °C	
[Icw] Rated Short-Time Withstand Current	25 kA during 0.5 s conforming to IEC 60947-3 4 kA during 20 s conforming to IEC 60947-3	
[Icm] Rated Short-Circuit Making Capacity	52 kA 690 V AC at 50/60 Hz	
[Ue] Rated Operational Voltage	690 V AC 50/60 Hz conforming to IEC 60947-3	
Contact Position Indicator	Yes	
Visible Break	No	
Mechanical Durability	6000 cycles conforming to IEC 60947-3	
Electrical Durability	1000 cycles 440 V AC 50/60 Hz conforming to IEC 60947-3	
Connection Pitch 70 mm		

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Height	327 mm
Width	280 mm
Depth	147 mm
Net Weight	18 kg

### **Environment**

Standards	IEC 60947-3
Product Certifications	ASTA ASEFA
Pollution Degree	3 conforming to IEC 60947-3
Ambient Air Temperature For Operation	-2570 °C
Ambient Air Temperature For Storage	-5085 °C

# **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	32.0 cm
Package 1 Width	25.0 cm
Package 1 Length	30.0 cm
Package 1 Weight	13.717 kg

## **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance



Mercury Free



Rohs Exemption Information

Yes

### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information