Product datasheet





Acti 9 iID - RCCB - 2P - 100A -100mA - type AC

A9R12291

Main

| Range | Acti9 | |
|-------------------------------------|---|--|
| Product Name | Acti9 iID | |
| Product Or Component Type | Residual current circuit breaker (RCCB) | |
| Device Short Name | ilD | |
| Poles Description | 2P | |
| Neutral Position | Left | |
| [In] Rated Current | 100 A | |
| Network Type | AC | |
| Earth-Leakage Sensitivity | 100 mA | |
| Earth-Leakage Protection Time Delay | Instantaneous | |
| Earth-Leakage Protection Class | Type AC | |

Complementary

| • | |
|---|-------------------------|
| Device Location In System | Outgoer |
| Network Frequency | 50/60 Hz |
| [Ue] Rated Operational Voltage | 220240 V AC 50/60 Hz |
| Residual Current Tripping Technology | Voltage independent |
| Rated Breaking And Making Capacity | ldm 1500 A Im 1500 A |
| Rated Conditional Short-Circuit Current | 10 kA |
| [Ui] Rated Insulation Voltage | 500 V AC 50/60 Hz |
| [Uimp] Rated Impulse Withstand Voltage | 6 kV |
| Surge Current | 250 A |
| Contact Position Indicator | Yes |
| Control Type | Toggle |
| Mounting Mode | Clip-on |
| Mounting Support | DIN rail |
| 9 Mm Pitches | 4 |
| Height | 91 mm |
| Width | 36 mm |
| Depth | 73.5 mm |

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

| Net Weight | 0.21 kg | |
|--|--|--|
| Colour | White | |
| Mechanical Durability | 20000 cycles | |
| Electrical Durability | AC-1: 10000 cycles | |
| Locking Options Description | Padlocking device | |
| Connections - Terminals | Single terminal top or bottom 135 mm² rigid Single terminal top or bottom 125 mm² flexible Single terminal top or bottom 125 mm² flexible with ferrule | |
| Wire Stripping Length | Length 14 mm for top or bottom connection | |
| ightening Torque 3.5 N.m top or bottom | | |

Environment

| Standards | EN/IEC 61008-1 |
|---------------------------------------|---|
| Ip Degree Of Protection | IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529 |
| Pollution Degree | 3 |
| Electromagnetic Compatibility | 8/20 μs impulse withstand, 250 A conforming to EN/IEC 61008-1 |
| Ambient Air Temperature For Operation | -560 °C |
| Ambient Air Temperature For Storage | -4085 °C |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|-----------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 8.100 cm |
| Package 1 Width | 4.000 cm |
| Package 1 Length | 10.000 cm |
| Package 1 Weight | 211.000 g |
| Unit Type Of Package 2 | S03 |
| Number Of Units In Package 2 | 54 |
| Package 2 Height | 30.000 cm |
| Package 2 Width | 30.000 cm |
| Package 2 Length | 40.000 cm |
| Package 2 Weight | 11.883 kg |

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

| Ø | Mercury Free | |
|----------|------------------------------------|-----|
| ⊘ | Rohs Exemption Information | Yes |
| ② | Halogen Free Plastic Parts Product | |

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|---|
| Eu Rohs Directive | Compliant with Exemptions |
| China Rohs Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile | No need of specific recycling operations |