Product datasheet

Specifications





Acti 9 iID - RCCB - 4P - 40A -300mA - type AC

A9R74440

Main

| Range | Acti9 |
|--|---|
| Product Name | Acti9 iID |
| Product Or Component Type | Residual current circuit breaker (RCCB) |
| Device Short Name | ilD |
| Poles Description | 4P |
| Neutral Position | Left |
| [In] Rated Current | 40 A |
| Network Type | AC |
| Earth-Leakage Sensitivity | 300 mA |
| Earth-Leakage Protection Time Delay | Instantaneous |
| Earth-Leakage Protection Class | Туре АС |

Complementary

| Device Location In System | Outgoer |
|--|-------------------------|
| Network Frequency | 50/60 Hz |
| [Ue] Rated Operational Voltage | 380415 V AC 50/60 Hz |
| Residual Current Tripping Technology | Voltage independent |
| Rated Breaking And Making Capacity | ldm 1500 A Im 1500 A |
| Rated Conditional Short-Circuit Current | 10 kA |
| [Ui] Rated Insulation Voltage | 500 V AC 50/60 Hz |
| [Uimp] Rated Impulse Withstand Voltage | 6 kV |
| Contact Position Indicator | Yes |
| Control Type | Toggle |
| Mounting Mode | Clip-on |
| Mounting Support | DIN rail |
| 9 Mm Pitches | 8 |
| Height | 91 mm |
| Width | 72 mm |
| Depth | 73.5 mm |
| Net Weight | 0.37 kg |

Excluding VAT, FCA Jabal Ali & are subject to change - check with your local distributor.

| Colour | White | |
|-----------------------------|--|--|
| Mechanical Durability | 20000 cycles | |
| Electrical Durability | AC-1: 15000 cycles | |
| Locking Options Description | Padlocking device | |
| Connections - Terminals | Single terminal top or bottom 135 mm² rigid Single terminal top or bottom 125 mm² flexible Single terminal top or bottom 125 mm² flexible with ferrule | |
| Wire Stripping Length | 14 mm for top or bottom connection | |
| Tightening Torque | 3.5 N.m top or bottom | |

Environment

| Standards | EN/IEC 61008-1 |
|--|--|
| Product Certifications | SNI |
| Ip Degree Of Protection | IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529 |
| Pollution Degree | 3 |
| Electromagnetic Compatibility | $8/20\ \mu s$ impulse withstand, 250 A conforming to EN/IEC 61008-1 |
| Ambient Air Temperature For Operation | -560 °C |
| Ambient Air Temperature For Storage | -4085 °C |

Packing Units

| Unit Type Of Package 1PCENumber Of Units In Package 11Package 1 Height7.5 cmPackage 1 Width8.4 cmPackage 1 Length10.0 cmPackage 1 Weight355.0 gUnit Type Of Package 2S03Number Of Units In Package 227Package 2 Height30.0 cmPackage 2 Width30.0 cmPackage 2 Width10.274 kg | | |
|---|------------------------------|-----------|
| Package 1 Height7.5 cmPackage 1 Width8.4 cmPackage 1 Length10.0 cmPackage 1 Weight355.0 gUnit Type Of Package 2S03Number Of Units In Package 227Package 2 Height30.0 cmPackage 2 Width30.0 cmPackage 2 Length40.0 cm | Unit Type Of Package 1 | PCE |
| Package 1 Width8.4 cmPackage 1 Length10.0 cmPackage 1 Weight355.0 gUnit Type Of Package 2S03Number Of Units In Package 227Package 2 Height30.0 cmPackage 2 Width30.0 cmPackage 2 Length40.0 cm | Number Of Units In Package 1 | 1 |
| Package 1 Length10.0 cmPackage 1 Weight355.0 gUnit Type Of Package 2S03Number Of Units In Package 227Package 2 Height30.0 cmPackage 2 Width30.0 cmPackage 2 Length40.0 cm | Package 1 Height | 7.5 cm |
| Package 1 Weight355.0 gUnit Type Of Package 2S03Number Of Units In Package 227Package 2 Height30.0 cmPackage 2 Width30.0 cmPackage 2 Length40.0 cm | Package 1 Width | 8.4 cm |
| Unit Type Of Package 2 \$03 Number Of Units In Package 2 27 Package 2 Height 30.0 cm Package 2 Width 30.0 cm Package 2 Length 40.0 cm | Package 1 Length | 10.0 cm |
| Number Of Units In Package 2 27 Package 2 Height 30.0 cm Package 2 Width 30.0 cm Package 2 Length 40.0 cm | Package 1 Weight | 355.0 g |
| Package 2 Height 30.0 cm Package 2 Width 30.0 cm Package 2 Length 40.0 cm | Unit Type Of Package 2 | S03 |
| Package 2 Width 30.0 cm Package 2 Length 40.0 cm | Number Of Units In Package 2 | 27 |
| Package 2 Length 40.0 cm | Package 2 Height | 30.0 cm |
| | Package 2 Width | 30.0 cm |
| Package 2 Weight 10.274 kg | Package 2 Length | 40.0 cm |
| | Package 2 Weight | 10.274 kg |

Contractual warranty

Warranty

18 months

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Mercury Free
Rohs Exemption Information Yes
Halogen Free Plastic Parts Product

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|---|
| Eu Rohs Directive | Compliant with Exemptions |
| China Rohs Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |