# **Product datasheet**

Specifications





Circuit breaker ComPacT NSX160F, 36kA at 415VAC, TMD trip unit 125A, 50 degrees C, 4 poles 3D

C16F6TM125C

### Main

····a···			
Range	ComPacT new generation		
Product Name	ComPacT NSX new generation		
Device Short Name	NSX160F		
Product Or Component Type	Circuit breaker		
Device Application	Distribution		
Poles Description	4P		
Protected Poles Description	3D		
Neutral Position	Left		
[In] Rated Current	125 A at 40 °C		
[Ue] Rated Operational Voltage	690 V AC 50/60 Hz		
Network Type	AC		
Network Frequency	50/60 Hz		
Suitability For Isolation	Yes conforming to EN/IEC 60947-2		
Utilisation Category	gory Category A		
[Icu] Rated Ultimate Short-Circuit Breaking Capacity	85 kA Icu at 220/240 V AC 50/60 Hz conforming to IEC 60947-2 36 kA Icu at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 35 kA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2 30 kA Icu at 500 V AC 50/60 Hz conforming to IEC 60947-2 22 kA Icu at 525 V AC 50/60 Hz conforming to IEC 60947-2 8 kA Icu at 660/690 V AC 50/60 Hz conforming to IEC 60947-2		
Performance Level	F 36 kA 415 V AC		
Trip Unit Name	TM-D		
Trip Unit Technology	Thermal-magnetic		
Trip Unit Protection Functions	Ц		
Control Type	Toggle		
Circuit Breaker Mounting Mode	Fixed		

### Complementary

[Ui] Rated Insulation Voltage	800 V AC 50/60 Hz	
[Uimp] Rated Impulse Withstand Voltage	8 kV	
[Ics] Rated Service Short-Circuit Breaking Capacity	85 kA at 220/240 V AC 50/60 Hz conforming to IEC 60947-2 36 kA at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 35 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2 30 kA at 500 V AC 50/60 Hz conforming to IEC 60947-2 22 kA at 525 V AC 50/60 Hz conforming to IEC 60947-2 8 kA at 660/690 V AC 50/60 Hz conforming to IEC 60947-2	

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Mechanical Durability	40000 cycles	
Electrical Durability	40000 cycles at 440 V In/2 20000 cycles at 440 V In 15000 cycles at 690 V In/2 7500 cycles at 690 V In	
Power Dissipation Per Pole	10.78 W	
Mounting Support	Backplate	
Mounting Position	Horizontal and vertical Flat on the back	
Upside Connection	Front	
Downside Connection	Front	
Connection Pitch	35 mm	
Protection Type	L : for overload protection (thermal) I : for short-circuit protection (magnetic)	
Trip Unit Rating	125 A at 50 °C	
Long-Time Pick-Up Adjustment Type Ir (Thermal Protection)	Adjustable	
[Ir] Long-Time Protection Pick-Up Adjustment Range	0.71 x ln	
Long-Time Protection Delay Adjustment Type Tr	Fixed	
[Tr] Long-Time Protection Delay Adjustment Range	120400 s at 1.5 x ln 15 s at 6 x lr	
Neutral Protection Settings	No protection (3D)	
Instantaneous Protection Pick-Up Adjustment Type Ii	Fixed	
[li] Instantaneous Protection Pick- Up Adjustment Range	1250 A	
Earth-Leakage Protection	Without	
Number Of Slots For Electrical Auxiliaries	5 slot(s)	
Width (W)	140 mm	
Height (H)	161 mm	
Depth (D)	86 mm	
Net Weight	2.6 kg	

### **Environment**

Standards	EN/IEC 60947	
Product Certifications	CCC EAC Marine	
Overvoltage Category	Class II	
Electrical Shock Protection Class	Class II	
Pollution Degree	3 conforming to IEC 60664-1	
Ip Degree Of Protection	IP40 conforming to IEC 60529	
Ik Degree Of Protection	IK07 conforming to IEC 62262	
Ambient Air Temperature For Operation	-2570 °C	
Ambient Air Temperature For Storage	-5085 °C	
Relative Humidity	095 %	

Operating Altitude 0...2000 m without derating 2000 m...5000 m with derating

# **Packing Units**

Unit Type Of Package 1	PCE		
------------------------	-----	--	--

Number Of Units In Package 1

## Sustainability Screen Premium

**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance



Mercury Free



Rohs Exemption Information

Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration  Compliant with Exemptions		
Eu Rohs Directive			
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information		
Environmental Disclosure	Product Environmental Profile		
Circularity Profile	End of Life Information		