Product datasheet

Specification





13A Twin Gang Switched Socket with 2.1A USB, White

E82T25USB_WE_G12

Main

Range	Pieno	
Product Or Component Type	Power socket-outlet + USB charger	
Device Presentation	Mechanism	
Socket Additional Information	Shuttered	
Colour Tint	White	
Load Type	No inductive load	

Complementary

Socket Number	1	
Device Mounting	Flush 47 mm	
Switch Function	ON/OFF power-socket outlet	
Number Of Power Socket Outlets	s 2 x 2P + E with shutters, British	
Rated Current	Power circuit: 13 A 220250 V, AC, 50/60 Hz	
Surface Finish	Glossy	
Surface Treatment	Untreated	
Number Of Gangs	2 gangs	
Connector Type	USB type A	
[Ue] Rated Operational Voltage	220250 V AC 50/60 Hz	
Maximum Power Consumption In W	0.075 W	
Input Power	16 W	
Integrated Connection Type	2 USB port 5 V DC, maximum load current: 2.1 A	
Material	Polycarbonate: grid plate Polycarbonate: cover Polycarbonate: surround Polycarbonate: dolly Nylon + GF: shutter Brass: contact plate Steel: spring Nickel steel: terminal screw	
Protection Type	USB port: over temperature protection with PWM IC circuit USB port: over voltage protection against surges with PWM IC circuit USB port: overcurrent between output phases and earth (on power up only) with PWM IC circuit	
Shape Of Screw Head	Cross	
Screwdriver Shape	Philips	
Electrical Connection	3 screw terminal	

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Clamping Connection Capacity	1 x 4 mm² for solid cable(s)
	2 x 4 mm² for stranded cable(s)
	1 x 2.5 mm ²
	2 x 2.5 mm ²
Wire Stripping Length	1012 mm
Mounting Support	Mounting box conforming to BS 4662
Fixing Mode By screws M3.5 x 25 mm	
Fixing Center	120.6 mm
Product Compatibility	Apple
	HW
	Power bank
	Tablet PC
	XiaoMi
	Smartphone
	Samsung
	HTC
Height	147 mm
Vidth 87 mm	
Depth	38.6 mm
Embedding Depth	29.5 mm
Net Weight	0.166 kg

Environment

Operating Altitude	<= 2000 m	
Ambient Air Temperature For Operation	040 °C	
Ambient Air Temperature For Storage	-5…60 °C	
Relative Humidity	095 %	
Standards	IEC 60950-1 BS 1363-2	
Product Certifications	IEC	
Ip Degree Of Protection	IP20	
Environmental Characteristic	Liquid soap Alcohol	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.9 cm
Package 1 Width	8.7 cm
Package 1 Length	14.7 cm
Package 1 Weight	171.0 g
Unit Type Of Package 2	CAR
Number Of Units In Package 2	5
Package 2 Height	9.5 cm
Package 2 Width	15.0 cm
Package 2 Length	19.0 cm
Package 2 Weight	905.0 g



Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

	Toxic Heavy Metal Free	
⊘	Mercury Free	
②	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information