Product datasheet

Specifications



8

Easy9 switch disconnector - 4P - 40 A - 400 V

EZ9S16440

Main

Range	Easy9
Product Or Component Type	Switch
Device Short Name	Easy9 switch
Switch Application	Distribution
Poles	4P
Utilisation Category	AC-22A
Suitability For Isolation	Yes

Complementary

[Ie] Rated Operational Current	40 A at 400 V 50/60 Hz
[Ue] Rated Operational Voltage	400 V AC 50/60 Hz
[Icm] Rated Short-Circuit Making Capacity	0.6 kA
[Icw] Rated Short-Time Withstand Current	0.48 kA during 1 s
[Ui] Rated Insulation Voltage	500 V AC 50/60 Hz
[Uimp] Rated Impulse Withstand Voltage	4 KV
Control Type	Toggle
Local Signalling	ON/OFF indication
Contact Position Indicator	Yes
Mounting Mode	Clip-on
Mounting Support	DIN rail
9 Mm Pitches	8
Height	81 mm
Width	72 mm
Depth	66.5 mm
Colour	Grey
Mechanical Durability	8500 cycles
Electrical Durability	1500 cycles
Connections - Terminals	Tunnel type terminal (top or bottom) 135 mm² rigid Tunnel type terminal (top or bottom) 125 mm² flexible
Tightening Torque	3.5 N.m

Excluding VAT, FCA Jabal Ali & are subject to change - check with your local distributor.

Standards	IEC 60947-3
Product Certifications	CE
Ip Degree Of Protection	IP20 conforming to IEC 60529
Tropicalisation	2
Ambient Air Temperature For Operation	-555 °C
Ambient Air Temperature For Storage	-570 °C

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	7.75 cm
Package 1 Width	7.21 cm
Package 1 Length	8.55 cm
Package 1 Weight	326 g
Unit Type Of Package 2	BB2
Number Of Units In Package 2	3
Package 2 Height	8.22 cm
Package 2 Width	8.86 cm
Package 2 Length	22.34 cm
Package 2 Weight	1044 g

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
	Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations