Product datasheet

Specifications





EasyPact TVS contactor 3P(3 NO) - AC-3 - <= 440 V 25A - 24 V AC coil

LC1E2510B5

Main

Range	Easy TeSys	
Range Of Product	Easy TeSys Control	
Product Or Component Type	Contactor	
Device Short Name	LC1E	
Contactor Application	Motor control Resistive load	
Utilisation Category	AC-1 AC-3	
Poles Description	3P	
[Ue] Rated Operational Voltage	Power circuit: <= 690 V AC 50/60 Hz	
[le] Rated Operational Current	25 A (at <55 °C) at <= 440 V AC AC-3 for power circuit 36 A (at <55 °C) at <= 440 V AC AC-1 for power circuit	
[Uc] Control Circuit Voltage	24 V AC 50 Hz	

Complementary

Motor Power Kw	5.5 kW at 220230 V AC 50/60 Hz (AC-3)
	11 kW at 380400 V AC 50/60 Hz (AC-3)
	11 kW at 415 V AC 50/60 Hz (AC-3)
	11 kW at 440 V AC 50/60 Hz (AC-3)
	15 kW at 500 V AC 50/60 Hz (AC-3)
	15 kW at 660690 V AC 50/60 Hz (AC-3)
Pole Contact Composition	3 NO
[Ith] Conventional Free Air Thermal Current	36 A (at 55 °C)
Irms Rated Making Capacity	250 A at 440 V AC for power circuit conforming to IEC 60947-4-1
Rated Breaking Capacity	200 A at 440 V for power circuit conforming to IEC 60947
[Icw] Rated Short-Time Withstand Current	240 A 40 °C - 10 s for power circuit
	120 A 40 °C - 60 s for power circuit
	50 A 40 °C - 600 s for power circuit
Associated Fuse Rating	10 A gG at <= 690 V coordination type 1 for control circuit conforming to IEC
	60947-5-1
	40 A gG at <= 690 V coordination type 1 for power circuit
Average Impedance	2.5 mOhm - Ith 36 A 50 Hz for power circuit
Power Dissipation Per Pole	1.6 W AC-3
	3.2 W AC-1
[Ui] Rated Insulation Voltage	690 V conforming to IEC 60947-4-1
Overvoltage Category	III
Pollution Degree	3

Excluding VAT, FCA Jabal Ali & are subject to change - check with your local distributor.

[Uimp] Rated Impulse Withstand Voltage	6 kV coil not connected to the power circuit conforming to IEC 60947
Mechanical Durability	1000000 cycles
Electrical Durability	1200000 cycles AC-3
	350000 cycles AC-1
Control Circuit Type	AC at 50 Hz
Control Circuit Voltage Limits	0.851.1 Uc (-555 °C):operational 50 Hz
	0.30.6 Uc (-555 °C):drop-out 50 Hz
Inrush Power In Va	95 VA 50 Hz cos phi 0.75 (at 20 °C)
	95 VA 60 Hz cos phi 0.75 (at 20 °C)
Hold-In Power Consumption In Va	8.3 VA 50 Hz cos phi 0.3 (at 20 °C)
	8.5 VA 60 Hz cos phi 0.3 (at 20 °C)
Heat Dissipation	23 W for control circuit
Operating Time	1222 ms on closing
	419 ms on opening
Maximum Operating Rate	1800 cyc/h 60 °C
Connections - Terminals	Control circuit: screw clamp terminals 1 14 mm ² - cable stiffness: flexible without
	cable end
	Control circuit: screw clamp terminals 2 14 mm ² - cable stiffness: flexible without cable end
	Control circuit: screw clamp terminals 1 14 mm ² - cable stiffness: flexible with cable
	end
	Control circuit: screw clamp terminals 2 12.5 mm ² - cable stiffness: flexible with
	cable end Control circuit: screw clamp terminals 1 14 mm ² - cable stiffness: solid without
	cable end
	Control circuit: screw clamp terminals 2 14 mm ² - cable stiffness: solid without
	cable end Power circuit: screw clamp terminals 1 1.56 mm ² - cable stiffness: solid without
	cable end
	Power circuit: screw clamp terminals 2 1.56 mm ² - cable stiffness: solid without
	cable end Power circuit: screw clamp terminals 1 16 mm ² - cable stiffness: flexible with cable
	Power circuit. Screw clamp terminals 1 16 mm - cable stimess. nexible with cable
	end
	end Power circuit: screw clamp terminals 2 14 mm ² - cable stiffness: flexible with cable
Tightening Torque	Power circuit: screw clamp terminals 2 14 mm ² - cable stiffness: flexible with cable
Tightening Torque	Power circuit: screw clamp terminals 2 14 mm ² - cable stiffness: flexible with cable end
	Power circuit: screw clamp terminals 2 14 mm ² - cable stiffness: flexible with cable end Control circuit: 1.2 N.m
Auxiliary Contact Composition	Power circuit: screw clamp terminals 2 14 mm ² - cable stiffness: flexible with cable end Control circuit: 1.2 N.m Power circuit: 1.5 N.m
Auxiliary Contact Composition Minimum Switching Voltage	Power circuit: screw clamp terminals 2 14 mm ² - cable stiffness: flexible with cable end Control circuit: 1.2 N.m Power circuit: 1.5 N.m 1 NO
Auxiliary Contact Composition Minimum Switching Voltage Minimum Switching Current	Power circuit: screw clamp terminals 2 14 mm ² - cable stiffness: flexible with cable end Control circuit: 1.2 N.m Power circuit: 1.5 N.m 1 NO 17 V for control circuit
Auxiliary Contact Composition Minimum Switching Voltage Minimum Switching Current Insulation Resistance	Power circuit: screw clamp terminals 2 14 mm² - cable stiffness: flexible with cable end Control circuit: 1.2 N.m Power circuit: 1.5 N.m 1 NO 17 V for control circuit 5 mA for control circuit > 10 MOhm for control circuit 1.5 ms on energisation guaranteed between NC and NO contact
Tightening Torque Auxiliary Contact Composition Minimum Switching Voltage Minimum Switching Current Insulation Resistance Non-Overlap Time	Power circuit: screw clamp terminals 2 14 mm ² - cable stiffness: flexible with cable end Control circuit: 1.2 N.m Power circuit: 1.5 N.m 1 NO 17 V for control circuit 5 mA for control circuit > 10 MOhm for control circuit

Environment

Standards	IEC 60947-1 IEC 60947-4-1 IEC 60947-5-1	
Product Certifications	EAC CE	
Ip Degree Of Protection	IP2X conforming to IEC 60529	
Protective Treatment	TH (pollution degree 3) conforming to IEC 60068-2-30 test Db	

Permissible Ambient Air Temperature Around The Device	-2070 °C at Uc -6080 °C storage -555 °C operation
Operating Altitude	3000 m without derating
Fire Resistance	850 °C conforming to IEC 60695-2-1
Mechanical Robustness	Vibrations contactor open (1.5 Gn, 5300 Hz) Vibrations contactor closed (3 Gn, 5300 Hz) Shocks contactor closed (10 Gn for 11 ms) Shocks contactor open (6 Gn for 11 ms)
Height	74 mm
Width	45 mm
Depth	85 mm
Net Weight	0.36 kg

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	8.68 cm
Package 1 Width	7.4 cm
Package 1 Length	4.82 cm
Package 1 Weight	359 g
Unit Type Of Package 2	S02
Number Of Units In Package 2	36
Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	13.332 kg

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information