Product datasheet





EasyPact TVS contactor 3P(3 NO) - AC-3 - <= 440 V 32A - 220 V AC coil

LC1E3210M5

Main

| Range | Easy TeSys | |
|---|---|--|
| Range Of Product | Easy TeSys Control | |
| Product Or Component Type | Contactor | |
| Device Short Name | LC1E | |
| Contactor Application | Motor control Resistive load | |
| Utilisation Category | AC-1 AC-3 | |
| Poles Description | 3P | |
| [Ue] Rated Operational Voltage | Power circuit: <= 690 V AC 50/60 Hz | |
| [le] Rated Operational Current | 32 A (at <55 $^{\circ}$ C) at <= 440 V AC AC-3 for power circuit 50 A (at <60 $^{\circ}$ C) at <= 440 V AC AC-1 for power circuit | |
| c] Control Circuit Voltage 220 V AC 50 Hz | | |

Complementary

| Motor Power Kw | 7.5 kW at 220230 V AC 50/60 Hz 15 kW at 380400 V 15 kW at 415 V 15 kW at 440 V 18.5 kW at 500 V 18.5 kW at 660690 V | |
|--|---|--|
| Pole Contact Composition | 3 NO | |
| [Ith] Conventional Free Air Thermal Current | 50 A (at 55 °C) | |
| Irms Rated Making Capacity 320 A at 440 V AC for power circuit conforming to IEC 60947-4-1 | | |
| Rated Breaking Capacity 256 A at 440 V for power circuit conforming to IEC 60947 | | |
| [Icw] Rated Short-Time Withstand Current | 260 A 40 °C - 10 s for power circuit 138 A 40 °C - 60 s for power circuit 60 A 40 °C - 600 s for power circuit | |
| Associated Fuse Rating | 10 A gG at <= 690 V coordination type 1 for control circuit conforming to IEC 60947-5-1 63 A gG at <= 690 V coordination type 1 for power circuit | |
| Average Impedance | 2.5 mOhm - Ith 50 A 50 Hz for power circuit | |
| Power Dissipation Per Pole 2 W AC-3 5 W AC-1 | | |
| [Ui] Rated Insulation Voltage | 690 V conforming to IEC 60947-4-1 | |
| Overvoltage Category | III | |
| Pollution Degree | 3 | |

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

| [Uimp] Rated Impulse Withstand Voltage | 6 kV coil not connected to the power circuit conforming to IEC 60947 | |
|--|---|--|
| Mechanical Durability | 8000000 cycles | |
| Electrical Durability | 1000000 cycles AC-3 350000 cycles AC-1 | |
| Control Circuit Type | AC at 50 Hz | |
| Control Circuit Voltage Limits | 0.851.1 Uc (-555 °C):operational 50 Hz 0.30.6 Uc (-555 °C):drop-out 50 Hz | |
| Inrush Power In Va | 95 VA 50 Hz cos phi 0.75 (at 20 °C) 95 VA 60 Hz cos phi 0.75 (at 20 °C) | |
| Hold-In Power Consumption In Va | 8.3 VA 50 Hz cos phi 0.3 (at 20 °C) 8.5 VA 60 Hz cos phi 0.3 (at 20 °C) | |
| Heat Dissipation | 23 W for control circuit | |
| Operating Time | 1222 ms on closing 419 ms on opening | |
| Maximum Operating Rate | 1800 cyc/h 60 °C | |
| Connections - Terminals | Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 2 12.5 mm² - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: solid without cable end Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: solid without cable end Power circuit: screw clamp terminals 1 1.56 mm² - cable stiffness: solid without cable end Power circuit: screw clamp terminals 2 1.56 mm² - cable stiffness: solid without cable end Power circuit: screw clamp terminals 1 16 mm² - cable stiffness: flexible with cable end Power circuit: screw clamp terminals 1 16 mm² - cable stiffness: flexible with cable end | |
| Tightening Torque | Control circuit: 1.2 N.m Power circuit: 2.1 N.m | |
| Auxiliary Contact Composition | 1 NO | |
| Minimum Switching Voltage | 17 V for control circuit | |
| Minimum Switching Current | 5 mA for control circuit | |
| Insulation Resistance | > 10 MOhm for control circuit | |
| Non-Overlap Time | 1.5 ms on energisation guaranteed between NC and NO contact 1.5 ms on de-energisation guaranteed between NC and NO contact | |
| Mounting Support | DIN rail Plate | |
| Environment | | |
| Standards | IEC 60947-4-1 IEC 60947-1 IEC 60947-5-1 | |
| Product Certifications | EAC CE | |
| Ip Degree Of Protection | IP2X conforming to IEC 60529 | |
| Protective Treatment | TH (pollution degree 3) conforming to IEC 60068-2-30 test Db | |

| Permissible Ambient Air Temperature Around The Device | -2070 °C at Uc -6080 °C storage -555 °C operation | |
|--|--|--|
| Operating Altitude | 3000 m without derating | |
| Fire Resistance | 850 °C conforming to IEC 60695-2-1 | |
| Mechanical Robustness | Vibrations contactor open (1.5 Gn, 5300 Hz) Vibrations contactor closed (3 Gn, 5300 Hz) Shocks contactor closed (10 Gn for 11 ms) Shocks contactor open (6 Gn for 11 ms) | |
| Height | 84 mm | |
| Width | 56 mm | |
| Depth | 86 mm | |
| Net Weight 0.45 kg | | |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|-----------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 8.6 cm |
| Package 1 Width | 8.4 cm |
| Package 1 Length | 5.6 cm |
| Package 1 Weight | 449 g |
| Unit Type Of Package 2 | S02 |
| Number Of Units In Package 2 | 24 |
| Package 2 Height | 15 cm |
| Package 2 Width | 30 cm |
| Package 2 Length | 40 cm |
| Package 2 Weight | 11.184 kg |

Contractual warranty

Warranty 18 months

Sustainability Green Premium*

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

| ⊘ | Reach Free Of Svhc | |
|----------|----------------------------|-----|
| ⊘ | Toxic Heavy Metal Free | |
| ⊘ | Mercury Free | |
| ⊘ | Rohs Exemption Information | Yes |

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|---|
| Eu Rohs Directive | Compliant EU RoHS Declaration |
| China Rohs Regulation | China RoHS declaration |
| Environmental Disclosure | Product Environmental Profile |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile | End of Life Information |