Product datasheet

Specification





Motor Management, TeSys T, motor controller, CANopen, 6 logic inputs, 3 relay logic outputs, 0.4 to 8A, 24 VDC

LTMR08CBD

① To be discontinued

! Discontinued on: 1 Aug 2023

Main

Range	TeSys
Product Name	TeSys T
Device Short Name	LTMR
Product Or Component Type	Motor controller
Device Application	Equipment monitoring and control
Measurement Current	0.48 A
[Us] Rated Supply Voltage	24 V DC
Current Consumption	56127 mA
Supply Voltage Limits	20.426.24 V DC
Communication Port Protocol	CANopen
Bus Type	CANopen ISO 1198 interface, addressing 1127, transmission rate 101000 kbit/s, SUB-D 9 with 4 twisted shielded pairs cable CANopen ISO 1198 interface, addressing 1127, transmission rate 101000 kbit/s, terminal block with 4 twisted shielded pairs cable

Complementary

[Ui] Rated Insulation Voltage	690 V conforming to EN/IEC 60947-1
	690 V conforming to CSA C22.2 No 14
	690 V conforming to UL 508
[Uimp] Rated Impulse Withstand	6 kV current or voltage measurement circuit conforming to EN/IEC 60947-4-1
Voltage	0.8 kV communication circuit conforming to EN/IEC 60947-4-1
	0.8 kV supply, inputs and outputs conforming to EN/IEC 60947-4-1
Short-Circuit Withstand	100 kA conforming to EN/IEC 60947-4-1
Associated Fuse Rating	4 A gG for output
	0.5 A gG for control circuit
Protection Type	Overload (long time)
	Phase failure
	Load fluctuation
	Phase imbalance
	Reverse polarity protection
	Thermal protection
	Thermal overload protection
	Earth-leakage protection
	Power factor variation
	Overload
	Locked rotor
	Locked folds

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

3
Control circuit: 0.50.6 N.m flat screwdriver 3 mm
without cable end Control circuit: connector 2 cable(s) 0.21 mm² (AWG 24AWG 14) solid without cable end
without cable end Control circuit: connector 2 cable(s) 0.51.5 mm² (AWG 24AWG 14) flexible
cable end Control circuit: connector 2 cable(s) 0.21.5 mm² (AWG 24AWG 14) flexible
cable end Control circuit: connector 1 cable(s) 0.22.5 mm² (AWG 24AWG 14) solid without cable end Control circuit: connector 2 cable(s) 0.21 mm² (AWG 24AWG 14) flexible with
without cable end Control circuit: connector 1 cable(s) 0.22.5 mm² (AWG 24AWG 14) solid without
without cable end Control circuit: connector 1 cable(s) 0.252.5 mm² (AWG 24AWG 14) flexible
cable end Control circuit: connector 1 cable(s) 0.22.5 mm² (AWG 24AWG 14) flexible
Control circuit: connector 1 cable(s) 0.252.5 mm² (AWG 24AWG 14) flexible with
5.08 mm
III
1 % current 5 % active and reactive power
0,02 temperature
5 % earth fault current external measurement +/- 30 min/year internal clock
1 % voltage (100830 V) 3 % power factor
515 % earth fault current internal measurement
Imbalance current
Temperature Earth-fault current
Phase current I1, I2, I3 RMS
Average current lavg
1 NO + 1 NC fault signal 3 NO
1800 cyc/h
30 W (DC-13), le = 1.25 A, 500000 cycles (output)
480 VA (AC-15), le = 2 A, 500000 cycles (output)
5 A at 250 V AC for logic output 5 A at 30 V DC for logic output
2 Hz
Logic input: < 15 V and 215 mA for 15 ms
Logic input: < 5 V and <= 15 mA for 5 ms
7 mA
6
Phase fault and earth fault trip counters Fault recording
Trip history information
Running hours counter/operating time Waiting time after overload tripping
Motor control command recording
Starting current and time Event recording

Electromagnetic Compatibility	Electrostatic discharge, 3, 8 kV air, 6 kV contact, conforming to EN/IEC 61000-4-2 Radiated RF fields, 3, 10 V/m, conforming to EN/IEC 61000-4-3
	Fast transients immunity test (other circuits), level 3, 2 kV, conforming to EN/IEC 61000-4-4
	Fast transients immunity test (on supply and relay outputs), level 4, 4 kV, conforming
	to EN/IEC 61000-4-4 Voltage dips and interruptions immunity test, 70 %, 500 ms, conforming to EN/IEC
	61000-4-11
	Conducted RF disturbances, 10 V, conforming to EN/IEC 61000-4-6
	Temperature sensor: surges (serial mode), 0.5 kV, conforming to EN/IEC 61000-4-5 Temperature sensor: surges (common mode), 1 kV, conforming to EN/IEC 61000-4-5
	Control circuit: surges (serial mode), 1 kV, conforming to EN/IEC 61000-4-5
	Control circuit: surges (common mode), 1 kV, conforming to EN/IEC 61000-4-5
	Communication: surges (common mode), 2 kV, conforming to EN/IEC 61000-4-5
	Relay outputs and supply: surges (serial mode), 2 kV, conforming to EN/IEC
	61000-4-5 Relay outputs and supply: surges (common mode), 4 kV, conforming to EN/IEC
	61000-4-5
Width	91 mm
Height	61 mm
Depth	122.5 mm
Net Weight	0.53 kg
Web Services	Web server
Compatibility Code	LTMR
Environment	
Standards	EN 60947-4-1
	CSA C22.2 No 14
	IEC 60947-4-1
	UL 508 IACS E10
Product Certifications	ATEX
	C-Tick
	EAC
	LROS (Lloyds register of shipping)
	NOM
	BV
	RINA KERI
	ABS
	UL
	CSA
	DNV
	RMRoS GL
	CCC
Protective Treatment	12 x 24 hour cycles conforming to EN/IEC 60068-2-30
	48 h conforming to EN/IEC 60070-2-11
	TH conforming to EN/IEC 60068
Fire Resistance	650 °C conforming to EN/IEC 60695-2-12 960 °C conforming to UL 94
Ambient Air Temperature For	·
Ambient Air Temperature For Operation	-2060 °C
Ambient Air Temperature For Storage	-4080 °C
Operating Altitude	<= 2000 m without derating
Mechanical Robustness	Vibrations mounted on symmetrical rail: 1 Gn, 5300 Hz conforming to EN/IEC
	60068-2-6 Vibrations plate mounted: 4 Gn, 5300 Hz conforming to EN/IEC 60068-2-6
	Shocks half sine wave acceleration: 15 Gn for 11 ms conforming to EN/IEC 60068-2-27
la Danisa Of Bushadian	

Packing Units

Ip Degree Of Protection

IP20

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	7.0 cm
Package 1 Width	10.0 cm
Package 1 Length	13.5 cm
Package 1 Weight	510.0 g
Unit Type Of Package 2	S02
Number Of Units In Package 2	10
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	5.452 kg

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

Ø	Mercury Free
Ø	Rohs Exemption Information Yes
Ø	Pvc Free
Ø	Halogen Free Plastic Parts Product

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information