# **Product datasheet**





Advanced display, SpaceLogic HMI, v3, for AS/AS-B/AS-P, 10.1" high-resolution display, IP54

SXWADBUND10003

! Discontinued on: 1 Nov 2020

! To be discontinued

### Main

Operating System	Android 8.1	
Current Consumption	1.27 A	
Flame Retardance	UL94-V0	
Width	258 mm	
Mounting Mode	Panel-mounted	
Product Certifications	CE FCC UL 60950 RCM	
Embedding Depth	15.24 mm	
Net Weight	0.933 kg	
Product Or Component Type	HMI	
Height	195.6 mm	
Colour	White	
Enclosure Material	ABS/PC	
Range	SpaceLogic	
[In] Rated Current	1 A	
Ambient Air Temperature For Storage	-2060 °C	
Depth	25 mm	
Display Type	TFT LCD touchscreen	
Display Size	10.1 inch	
Ambient Air Temperature For Operation	040 °C	
Display Resolution	1280 x 800 pixels	
Memory Type	2 GB RAM	
Communication Port Protocol	USBNet: USB 2.0	
[Us] Rated Supply Voltage	24 V DC +/- 10 % 1524 V DC +/- 10 %	
Range Compatibility	SpaceLogic AS SpaceLogic AS-P SpaceLogic AS-B	

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.



Standards	EN 60950-1:2006+A11:2009+A1:2010+A12:2011+A2:2013 IEC 60950-1:ed. 2:2005+Am1:2009+Am2:2013 UL 60950-1:ed. 2:2014 CSA C22.2 No. 60950-1-07:ed. 2:2014 EN 55024:2010 FCC part 15 Subpart B class B	
Relative Humidity	095 % RH, non-condensing	
Number Of Port	1, connector type: USB type C	
Processor Name	Intel Celeron N3350 dual core at 1.1 GHz	
Communication Network Type	Network Type Wi-Fi IEEE 802.11 b/g/n at 2.4 GHz	

### **Environment**

Ip Degree Of Protection IP54

## **Packing Units**

•	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	11.500 cm
Package 1 Width	29.000 cm
Package 1 Length	36.500 cm
Package 1 Weight	1.333 kg
Unit Type Of Package 2	S03
Number Of Units In Package 2	2
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	3.086 kg
Unit Type Of Package 3	P06
Number Of Units In Package 3	16
Package 3 Height	75.000 cm
Package 3 Width	80.000 cm
Package 3 Length	60.000 cm
Package 3 Weight	32.688 kg



**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance

	Mercury Free	
<b>⊘</b>	Rohs Exemption Information	Yes
	Halogen Free Plastic Parts Product	

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information