

Product datasheet

Specifications



current transformer TI 400/5 A - for cable Ø 35 mm

16470

 **Discontinued on:** 17 Nov 2014

 **Discontinued**

Main

Range	PowerLogic
Product Name	CT
Product Or Component Type	Current transformer
Secondary Current	5 A
Accuracy Class	Class 0.5 at 8 VA Class 1 at 12 VA Class 3 at 15 VA
[In] Rated Current	400 A

Complementary

Current Transformer Type	Tropicalised for busbar and cable
Current Transformer Ratio	400/5
Maximum Safety Factor	5
[Ue] Rated Operational Voltage	< 720 V AC 50/60 Hz
Mounting Mode	Insulated locking screw
Mounting Support	Busbar Mounting plate DIN rail
Width	77 mm outside:
Height	107 mm outside:
Depth	64 mm outside:
Diameter	35 mm
Net Weight	0.43 kg
Cable Outer Diameter	35 mm - cable 0...240 mm ²
Opening Of Bars	40 x 10

Environment

Standards	IEC 60044-1 VDE 0414
Product Certifications	CE
Ip Degree Of Protection	IP20
Relative Humidity	95...100 %
Ambient Air Temperature For Operation	-25...60 °C

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Contractual warranty

Warranty	18 months
----------	-----------