


# Product datasheet

Specifications



MX shunt trip release, Compact NS80H-MA, Compact NSC100N, 220 VAC to 240 VAC 50/60 Hz

28072

Discontinued on: 30 Mar 2022

Discontinued

## Main

Range	ComPact
Range Of Product	NSC100 NG160 NSA125...160 NS80H-MA NG160NA
Device Short Name	MX
Product Or Component Type	Voltage release
Device Application	Control
Voltage Release Type	Shunt trip release
[Uc] Control Circuit Voltage	220...240 V AC 50/60 Hz
Range Compatibility	ComPact ComPact NS ComPact Compact NSC ComPact Compact NG

## Complementary

Operating Threshold	0.7...1.1 x Un
Control Signal Type	Maintained Impulse
Impulse Duration	>= 20 ms
Auxiliary Connection Terminal	Screw terminal 0...1.5 mm <sup>2</sup>

## Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1

## Contractual warranty

Warranty	18 months
----------	-----------

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



# Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



RoHS/REACH

## Certifications & Standards

Eu Rohs Directive

Pro-active compliance (Product out of EU RoHS legal scope)

[EU RoHS Declaration](#)

---