Product datasheet

Specifications

Green Premium™

Standard opening undervoltage release MN, MasterPact NT, ComPacT NS630b/NS1600, drawout, 200/250VDC, 200/250VAC

33822

Main

Range	MasterPacT
Range Of Product	MasterPact NT MasterPact NT NAVY ComPacT NS630b...1600 new generation
Device Short Name	MN
Product Or Component Type	Voltage release
Device Application	Control
Voltage Release Type	Opening coil Undervoltage release
Control Type	Standard
[Uc] Control Circuit Voltage	200...250 V AC 50/60 Hz 200...250 V DC
Circuit Breaker Mounting Mode	Drawout
Range Compatibility	Masterpact MasterPact NT ComPact ComPact NS630b...1600

Complementary

Operating Threshold	0.35...0.7 x Un opening 0.85 x Un closing
Response Time	40 ms +/- 5 % for MasterPact NT 90 ms +/- 5 % for Compact NS630b...1600
Supply Holding Power	4.5 VA

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.5 cm
Package 1 Width	6.0 cm
Package 1 Length	8.2 cm
Package 1 Weight	177.0 g

Contractual warranty

Warranty	18 months

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO_2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium ›

Guide to assess a product's sustainability ›

Transparency   RoHS/REACh

Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information   Yes

Certifications & Standards

Reach Regulation   REACh Declaration

Eu Rohs Directive   Pro-active compliance (Product out of EU RoHS legal scope)

China Rohs Regulation   China RoHS declaration

Product out of China RoHS scope. Substance declaration for your information

---

Environmental Disclosure   Product Environmental Profile

Circularity Profile   End of Life Information