Product datasheet

Specification





TeSys, Contactor, TeSys Deca, 3P(3NO), AC-3/AC-3e, <=440V, 150A, 24V DC standard coil, lugs/bars terminals

LC1D1506BD

Main

Range	TeSys	
Range Of Product	TeSys Deca	
Product Or Component Type	Contactor	
Device Short Name	LC1D	
Contactor Application	Motor control Resistive load	
Utilisation Category	AC-3 AC-1 AC-4 AC-3e	
Poles Description	3P	
[Ue] Rated Operational Voltage	Power circuit: <= 1000 V AC 25400 Hz Power circuit: <= 300 V DC	
[le] Rated Operational Current	200 A (at <60 °C) at <= 440 V AC AC-1 for power circuit 150 A (at <60 °C) at <= 440 V AC AC-3 for power circuit 150 A (at <60 °C) at <= 440 V AC AC-3e for power circuit	
[Uc] Control Circuit Voltage	24 V DC	

Complementary

Motor Power Kw	40 kW at 220230 V AC 50/60 Hz (AC-3)	
	75 kW at 380400 V AC 50/60 Hz (AC-3)	
	80 kW at 415440 V AC 50/60 Hz (AC-3)	
	90 kW at 500 V AC 50/60 Hz (AC-3)	
	100 kW at 660690 V AC 50/60 Hz (AC-3)	
	75 kW at 1000 V AC 50/60 Hz (AC-3)	
	22 kW at 400 V AC 50/60 Hz (AC-4)	
	40 kW at 220230 V AC 50/60 Hz (AC-3e)	
	75 kW at 380400 V AC 50/60 Hz (AC-3e)	
	80 kW at 415440 V AC 50/60 Hz (AC-3e)	
	90 kW at 500 V AC 50/60 Hz (AC-3e)	
	100 kW at 660690 V AC 50/60 Hz (AC-3e)	
	75 kW at 1000 V AC 50/60 Hz (AC-3e)	
Motor Power Hp	40 hp at 200/208 V AC 50/60 Hz for 3 phases motors	
	50 hp at 230/240 V AC 50/60 Hz for 3 phases motors	
	100 hp at 460/480 V AC 50/60 Hz for 3 phases motors	
	125 hp at 575/600 V AC 50/60 Hz for 3 phases motors	
Compatibility Code	LC1D	
Pole Contact Composition	3 NO	
Protective Cover	With	
[Ith] Conventional Free Air Thermal Current	200 A (at 60 °C) for power circuit	
Irms Rated Making Capacity	140 A AC for signalling circuit conforming to IEC 60947-5-1	
	250 A DC for signalling circuit conforming to IEC 60947-5-1	
	1660 A at 440 V for power circuit conforming to IEC 60947	

1400 A at 440 V for power circuit conforming to IEC 60947
250 A 40 °C - 10 min for power circuit
580 A 40 °C - 1 min for power circuit
1200 A 40 °C - 10 s for power circuit
1400 A 40 °C - 1 s for power circuit
100 A - 1 s for signalling circuit 120 A - 500 ms for signalling circuit
140 A - 100 ms for signalling circuit
10 A gG for signalling circuit conforming to IEC 60947-5-1
315 A gG at <= 690 V coordination type 1 for power circuit
250 A gG at <= 690 V coordination type 2 for power circuit
0.6 mOhm - Ith 200 A 50 Hz for power circuit
24 W AC-1
13.5 W AC-3 13.5 W AC-3e
Power circuit: 600 V CSA certified Power circuit: 600 V UL certified
Power circuit: 1000 V conforming to IEC 60947-4-1
Signalling circuit: 690 V conforming to IEC 60947-1
Signalling circuit: 600 V CSA certified
Signalling circuit: 600 V UL certified
III
3
8 kV conforming to IEC 60947
B10d = 684932 cycles contactor with nominal load conforming to EN/ISO 13849-1
B10d = 10000000 cycles contactor with mechanical load conforming to EN/ISO
13849-1
8 Mcycles
0.85 Mcycles 150 A AC-3 at Ue <= 440 V
1 Mcycles 200 A AC-1 at Ue <= 440 V
0.85 Mcycles 150 A AC-3e at Ue <= 440 V
DC standard
With integral suppression device
0.751.2 Uc (-4055 °C):operational DC
0.150.4 Uc (-4070 °C):drop-out DC
11.2 Uc (5570 °C):operational DC
270365 W (at 20 °C)
2.45.1 W at 20 °C
2035 ms closing
4075 ms opening
25 ms
1200 cyc/h 60 °C
Control circuit: lugs-ring terminals - external diameter: 8 mm
Power circuit: lugs-ring terminals - external diameter: 25 mm Power circuit: bars 1 - busbar cross section: 5 x 25 mm
Control circuit: 1.2 N.m - on lugs-ring terminals - with screwdriver flat Ø 6 mm M3.5
Control circuit: 1.2 N.m - on lugs-ring terminals - with screwdriver Philips No 2 M3.5
Power circuit: 12 N.m - on lugs-ring terminals hexagonal screw head 13 mm M8
Power circuit: 12 N.m - on bars hexagonal screw head 13 mm M8 Control circuit: 1.2 N.m - on lugs-ring terminals - with screwdriver pozidriv No 2 M3.5
1 NO + 1 NC
type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1 type mirror contact 1 NC conforming to IEC 60947-4-1
25400 Hz
17 V for signalling circuit

Minimum Switching Current	5 mA for signalling circuit
Insulation Resistance	> 10 MOhm for signalling circuit
Non-Overlap Time	1.5 ms on de-energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact
Mounting Support	Rail Plate

Environment

Environment	
Standards	CSA C22.2 No 14 EN 60947-4-1 EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1 UL 508
Product Certifications	GL CSA CCC UL DNV LROS (Lloyds register of shipping) RINA BV GOST UKCA CE
Ip Degree Of Protection	IP20 front face conforming to IEC 60529
Protective Treatment	TH conforming to IEC 60068-2-30
Climatic Withstand	conforming to IACS E10 exposure to damp heat
Permissible Ambient Air Temperature Around The Device	-4060 °C 6070 °C with derating
Operating Altitude	03000 m
Fire Resistance	850 °C conforming to IEC 60695-2-1
Flame Retardance	V1 conforming to UL 94
Mechanical Robustness	Vibrations contactor open (2 Gn, 5300 Hz) Vibrations contactor closed (4 Gn, 5300 Hz) Shocks contactor closed (15 Gn for 11 ms) Shocks contactor open (6 Gn for 11 ms)
Height	158 mm
Width	120 mm
Depth	136 mm
Net Weight	2.5 kg

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	19.000 cm
Package 1 Width	17.500 cm
Package 1 Length	21.500 cm
Package 1 Weight	2.207 kg
Unit Type Of Package 2	P06
Number Of Units In Package 2	27

Package 2 Height	75.000 cm	
Package 2 Width	60.000 cm	
Package 2 Length	80.000 cm	
Package 2 Weight	71.212 ka	

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information