# **Product datasheet**

Specification





TeSys; TeSys Deca, Contactor, 3P(3 NO), AC-3/AC-3e, 0 to 440V, 50A, 48 to 130VAC/DC coil, EverLink

LC1D50AEHE

### Main

Range	TeSys TeSys Deca
Range Of Product	TeSys Deca
Product Or Component Type	Contactor
Device Short Name	LC1D
Contactor Application	Resistive load Motor control
Utilisation Category	AC-1 AC-3 AC-3e
Poles Description	3P
[Ue] Rated Operational Voltage	Power circuit: <= 690 V AC 25400 Hz
[le] Rated Operational Current	80 A (at <60 °C) at <= 440 V AC-1 for power circuit 50 A (at <60 °C) at <= 440 V AC-3 for power circuit 50 A (at <60 °C) at <= 440 V AC-3e for power circuit
[Uc] Control Circuit Voltage	48130 V AC 50/60 Hz 48130 V DC

### Complementary

Motor Power Kw	15 kW at 220230 V AC 50 Hz (AC-3) 22 kW at 380400 V AC 50 Hz (AC-3) 25 kW at 415 V AC 50 Hz (AC-3) 30 kW at 440 V AC 50 Hz (AC-3) 30 kW at 500 V AC 50 Hz (AC-3) 33 kW at 660690 V AC 50 Hz (AC-3) 15 kW at 220230 V AC 50 Hz (AC-3e) 22 kW at 380400 V AC 50 Hz (AC-3e) 25 kW at 415 V AC 50 Hz (AC-3e) 30 kW at 440 V AC 50 Hz (AC-3e) 30 kW at 500 V AC 50 Hz (AC-3e) 30 kW at 500 V AC 50 Hz (AC-3e) 30 kW at 660690 V AC 50 Hz (AC-3e)
Motor Power Hp	3 hp at 115 V AC 60 Hz for 1 phase motors 7.5 hp at 230/240 V AC 60 Hz for 1 phase motors 15 hp at 200/208 V AC 60 Hz for 3 phases motors 15 hp at 230/240 V AC 60 Hz for 3 phases motors 40 hp at 460/480 V AC 60 Hz for 3 phases motors 40 hp at 575/600 V AC 60 Hz for 3 phases motors
Compatibility Code	LC1D
Pole Contact Composition	3 NO
Protective Cover	With
[Ith] Conventional Free Air Thermal Current	80 A (at 60 °C) for power circuit 10 A (at 60 °C) for signalling circuit

19 Apr 2024 Life Is On Schneider

Irms Rated Making Capacity	900 A at 440 V for power circuit conforming to IEC 60947
	140 A AC for signalling circuit conforming to IEC 60947-5-1
	250 A DC for signalling circuit conforming to IEC 60947-5-1
Rated Breaking Capacity	900 A at 440 V for power circuit conforming to IEC 60947
[Icw] Rated Short-Time Withstand	100 A - 1 s for signalling circuit
Current	120 A - 500 ms for signalling circuit
	140 A - 100 ms for signalling circuit
	84 A 40 °C - 10 min for power circuit
	208 A 40 °C - 1 min for power circuit
	400 A 40 °C - 10 s for power circuit
	810 A 40 °C - 1 s for power circuit
Associated Fuse Rating	10 A gG for signalling circuit conforming to IEC 60947-5-1
	100 A gG at <= 690 V coordination type 1 for power circuit
	100 A gG at <= 690 V coordination type 2 for power circuit
Average Impedance	1.5 mOhm - Ith 80 A 50 Hz for power circuit
Power Dissipation Per Pole	9.6 W AC-1
	3.7 W AC-3
	3.7 W AC-3e
[Ui] Rated Insulation Voltage	Power circuit: 690 V conforming to IEC 60947-4-1
	Signalling circuit: 690 V conforming to IEC 60947-1
Overvoltage Category	III
Pollution Degree	3
[Uimp] Rated Impulse Withstand Voltage	6 kV conforming to IEC 60947
Safety Reliability Level	B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO
Safety Reliability Level	
Safety Reliability Level  Mechanical Durability	B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO
Mechanical Durability	B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1  6 Mcycles
	B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1  6 Mcycles  1.8 Mcycles 42 A AC-3 at Ue <= 440 V
Mechanical Durability	B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1  6 Mcycles  1.8 Mcycles 42 A AC-3 at Ue <= 440 V  0.5 Mcycles 80 A AC-1 at Ue <= 440 V
Mechanical Durability  Electrical Durability	B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1  6 Mcycles  1.8 Mcycles 42 A AC-3 at Ue <= 440 V
Mechanical Durability	B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1  6 Mcycles  1.8 Mcycles 42 A AC-3 at Ue <= 440 V  0.5 Mcycles 80 A AC-1 at Ue <= 440 V
Mechanical Durability  Electrical Durability	B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1  6 Mcycles  1.8 Mcycles 42 A AC-3 at Ue <= 440 V  0.5 Mcycles 80 A AC-1 at Ue <= 440 V  1.8 Mcycles 42 A AC-3e at Ue <= 440 V
Mechanical Durability  Electrical Durability  Control Circuit Type  Coil Technology	B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1  6 Mcycles  1.8 Mcycles 42 A AC-3 at Ue <= 440 V  0.5 Mcycles 80 A AC-1 at Ue <= 440 V  1.8 Mcycles 42 A AC-3e at Ue <= 440 V  AC/DC at 50/60 Hz AC/DC electronic  Built-in bidirectional peak limiting
Mechanical Durability  Electrical Durability  Control Circuit Type	B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1  6 Mcycles  1.8 Mcycles 42 A AC-3 at Ue <= 440 V  0.5 Mcycles 80 A AC-1 at Ue <= 440 V  1.8 Mcycles 42 A AC-3e at Ue <= 440 V  AC/DC at 50/60 Hz AC/DC electronic  Built-in bidirectional peak limiting  <= 0.1 Uc (-4070 °C):drop-out AC/DC
Mechanical Durability  Electrical Durability  Control Circuit Type  Coil Technology	B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1  6 Mcycles  1.8 Mcycles 42 A AC-3 at Ue <= 440 V  0.5 Mcycles 80 A AC-1 at Ue <= 440 V  1.8 Mcycles 42 A AC-3e at Ue <= 440 V  AC/DC at 50/60 Hz AC/DC electronic  Built-in bidirectional peak limiting  <= 0.1 Uc (-4070 °C):drop-out AC/DC 0.851.1 Uc (-4060 °C):operational AC/DC
Mechanical Durability  Electrical Durability  Control Circuit Type  Coil Technology	B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1  6 Mcycles  1.8 Mcycles 42 A AC-3 at Ue <= 440 V  0.5 Mcycles 80 A AC-1 at Ue <= 440 V  1.8 Mcycles 42 A AC-3e at Ue <= 440 V  AC/DC at 50/60 Hz AC/DC electronic  Built-in bidirectional peak limiting  <= 0.1 Uc (-4070 °C):drop-out AC/DC
Mechanical Durability  Electrical Durability  Control Circuit Type  Coil Technology	B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1  6 Mcycles  1.8 Mcycles 42 A AC-3 at Ue <= 440 V  0.5 Mcycles 80 A AC-1 at Ue <= 440 V  1.8 Mcycles 42 A AC-3e at Ue <= 440 V  AC/DC at 50/60 Hz AC/DC electronic  Built-in bidirectional peak limiting  <= 0.1 Uc (-4070 °C):drop-out AC/DC 0.851.1 Uc (-4060 °C):operational AC/DC
Mechanical Durability  Electrical Durability  Control Circuit Type  Coil Technology  Control Circuit Voltage Limits	B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1  6 Mcycles  1.8 Mcycles 42 A AC-3 at Ue <= 440 V  0.5 Mcycles 80 A AC-1 at Ue <= 440 V  1.8 Mcycles 42 A AC-3e at Ue <= 440 V  AC/DC at 50/60 Hz AC/DC electronic  Built-in bidirectional peak limiting  <= 0.1 Uc (-4070 °C):drop-out AC/DC  0.851.1 Uc (-4060 °C):operational AC/DC  11.1 Uc (6070 °C):operational AC/DC
Mechanical Durability  Electrical Durability  Control Circuit Type  Coil Technology  Control Circuit Voltage Limits  Inrush Power In Va	B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1  6 Mcycles  1.8 Mcycles 42 A AC-3 at Ue <= 440 V  0.5 Mcycles 80 A AC-1 at Ue <= 440 V  1.8 Mcycles 42 A AC-3e at Ue <= 440 V  AC/DC at 50/60 Hz AC/DC electronic  Built-in bidirectional peak limiting  <= 0.1 Uc (-4070 °C):drop-out AC/DC  0.851.1 Uc (-4060 °C):operational AC/DC  11.1 Uc (6070 °C):operational AC/DC
Mechanical Durability  Electrical Durability  Control Circuit Type  Coil Technology  Control Circuit Voltage Limits  Inrush Power In Va  Inrush Power In W	B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1  6 Mcycles  1.8 Mcycles 42 A AC-3 at Ue <= 440 V  0.5 Mcycles 80 A AC-1 at Ue <= 440 V  1.8 Mcycles 42 A AC-3e at Ue <= 440 V  AC/DC at 50/60 Hz AC/DC electronic  Built-in bidirectional peak limiting  <= 0.1 Uc (-4070 °C):drop-out AC/DC  0.851.1 Uc (-4060 °C):operational AC/DC  11.1 Uc (6070 °C):operational AC/DC  23 VA 50/60 Hz (at 20 °C)  19 W (at 20 °C)
Mechanical Durability  Electrical Durability  Control Circuit Type  Coil Technology  Control Circuit Voltage Limits  Inrush Power In Va  Inrush Power In W  Hold-In Power Consumption In Va	B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1  6 Mcycles  1.8 Mcycles 42 A AC-3 at Ue <= 440 V 0.5 Mcycles 80 A AC-1 at Ue <= 440 V 1.8 Mcycles 42 A AC-3e at Ue <= 440 V AC/DC at 50/60 Hz AC/DC electronic  Built-in bidirectional peak limiting  <= 0.1 Uc (-4070 °C):drop-out AC/DC 0.851.1 Uc (-4060 °C):operational AC/DC 11.1 Uc (6070 °C):operational AC/DC 23 VA 50/60 Hz (at 20 °C)  19 W (at 20 °C)  1.4 VA 50/60 Hz (at 20 °C)
Mechanical Durability  Electrical Durability  Control Circuit Type  Coil Technology  Control Circuit Voltage Limits  Inrush Power In Va  Inrush Power In W  Hold-In Power Consumption In Va  Hold-In Power Consumption In W	B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1  6 Mcycles  1.8 Mcycles 42 A AC-3 at Ue <= 440 V  0.5 Mcycles 80 A AC-1 at Ue <= 440 V  1.8 Mcycles 42 A AC-3e at Ue <= 440 V  AC/DC at 50/60 Hz AC/DC electronic  Built-in bidirectional peak limiting  <= 0.1 Uc (-4070 °C):drop-out AC/DC  0.851.1 Uc (-4060 °C):operational AC/DC  11.1 Uc (6070 °C):operational AC/DC  23 VA 50/60 Hz (at 20 °C)  19 W (at 20 °C)  1.4 VA 50/60 Hz (at 20 °C)  0.9 W at 20 °C
Mechanical Durability  Electrical Durability  Control Circuit Type  Coil Technology  Control Circuit Voltage Limits  Inrush Power In Va  Inrush Power In W  Hold-In Power Consumption In Va  Hold-In Power Consumption In W  Heat Dissipation	B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1  6 Mcycles  1.8 Mcycles 42 A AC-3 at Ue <= 440 V  0.5 Mcycles 80 A AC-1 at Ue <= 440 V  1.8 Mcycles 42 A AC-3e at Ue <= 440 V  AC/DC at 50/60 Hz AC/DC electronic  Built-in bidirectional peak limiting  <= 0.1 Uc (-4070 °C):drop-out AC/DC  0.851.1 Uc (-4060 °C):operational AC/DC  11.1 Uc (6070 °C):operational AC/DC  23 VA 50/60 Hz (at 20 °C)  19 W (at 20 °C)  1.4 VA 50/60 Hz (at 20 °C)  0.9 W at 50/60 Hz  5565 ms closing
Mechanical Durability  Electrical Durability  Control Circuit Type  Coil Technology  Control Circuit Voltage Limits  Inrush Power In Va  Inrush Power In W  Hold-In Power Consumption In Va  Hold-In Power Consumption In W  Heat Dissipation	B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1  6 Mcycles  1.8 Mcycles 42 A AC-3 at Ue <= 440 V 0.5 Mcycles 80 A AC-1 at Ue <= 440 V 1.8 Mcycles 42 A AC-3e at Ue <= 440 V AC/DC at 50/60 Hz AC/DC electronic  Built-in bidirectional peak limiting  <= 0.1 Uc (-4070 °C):drop-out AC/DC 0.851.1 Uc (-4060 °C):operational AC/DC 11.1 Uc (6070 °C):operational AC/DC 23 VA 50/60 Hz (at 20 °C)  19 W (at 20 °C)  1.4 VA 50/60 Hz (at 20 °C)  0.9 W at 50/60 Hz  5565 ms closing 20120 ms opening (date code >= 17221)
Mechanical Durability  Electrical Durability  Control Circuit Type  Coil Technology  Control Circuit Voltage Limits  Inrush Power In Va  Inrush Power In W  Hold-In Power Consumption In Va  Hold-In Power Consumption In W  Heat Dissipation	B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1  6 Mcycles  1.8 Mcycles 42 A AC-3 at Ue <= 440 V  0.5 Mcycles 80 A AC-1 at Ue <= 440 V  1.8 Mcycles 42 A AC-3e at Ue <= 440 V  AC/DC at 50/60 Hz AC/DC electronic  Built-in bidirectional peak limiting  <= 0.1 Uc (-4070 °C):drop-out AC/DC  0.851.1 Uc (-4060 °C):operational AC/DC  11.1 Uc (6070 °C):operational AC/DC  23 VA 50/60 Hz (at 20 °C)  19 W (at 20 °C)  1.4 VA 50/60 Hz (at 20 °C)  0.9 W at 50/60 Hz  5565 ms closing

Connections - Terminals	Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: flexible without cable end
	Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: flexible without cable end
	Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: flexible with cable end
	Control circuit: screw clamp terminals 2 12.5 mm <sup>2</sup> - cable stiffness: flexible with cable end
	Control circuit: screw clamp terminals 1 14 mm² - cable stiffness: solid
	Control circuit: screw clamp terminals 2 14 mm² - cable stiffness: solid Power circuit: EverLink BTR screw connectors 1 135 mm² - cable stiffness: flexible without cable end
	Power circuit: EverLink BTR screw connectors 1 135 mm² - cable stiffness: flexible with cable end
	Power circuit: EverLink BTR screw connectors 1 135 mm² - cable stiffness: solid Power circuit: EverLink BTR screw connectors 2 125 mm² - cable stiffness: flexible without cable end
	Power circuit: EverLink BTR screw connectors 2 125 mm² - cable stiffness: flexible with cable end
	Power circuit: EverLink BTR screw connectors 2 125 mm² - cable stiffness: solid
Tightening Torque	Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2 Power circuit: 8 N.m - on EverLink BTR screw connectors - cable 2535 mm² hexagonal screw head 4 mm Power circuit: 5 N.m - on EverLink BTR screw connectors - cable 125 mm²
	hexagonal screw head 4 mm  Power circuit: 5 N.m - with screwdriver pozidriv No 2
	Control circuit: 1.7 N.m - with screwdriver pozidriv No 2
Auxiliary Contact Composition	1 NO + 1 NC
Auxiliary Contacts Type	type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1 type mirror contact 1 NC conforming to IEC 60947-4-1
Signalling Circuit Frequency	25400 Hz
Minimum Switching Voltage	17 V for signalling circuit
Minimum Switching Current	5 mA for signalling circuit
Insulation Resistance	> 10 MOhm for signalling circuit
Non-Overlap Time	1.5 ms on de-energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact
Mounting Support	Rail Plate
Environment	
Standards	EN/IEC 60947-4-1
	EN/IEC 60947-5-1 UL 60947-4-1
	CSA C22.2 No 60947-4-1 IEC 60335-1
Product Certifications	CCC
	CSA
	EAC UL
	KC
	DNV-GL
	LROS (Lloyds register of shipping) UKCA
Ip Degree Of Protection	IP20 front face conforming to IEC 60529
Climatic Withstand	conforming to IACS E10 exposure to damp heat conforming to IEC 60947-1 Annex Q category D exposure to damp heat
Permissible Ambient Air Temperature Around The Device	-40…60 °C 60…70 °C with derating
Operating Altitude	03000 m

850 °C conforming to IEC 60695-2-1

Fire Resistance

Flame Retardance	V1 conforming to UL 94	
Mechanical Robustness	Vibrations contactor open (2 Gn, 5300 Hz) Vibrations contactor closed (4 Gn, 5300 Hz) Shocks contactor open (10 Gn for 11 ms) Shocks contactor closed (15 Gn for 11 ms)	
Height	122 mm	
Width	55 mm	
Depth	120 mm	
Net Weight	0.997 kg	

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	6.2 cm
Package 1 Width	13.8 cm
Package 1 Length	15.5 cm
Package 1 Weight	1.058 kg
Unit Type Of Package 2	S02
Number Of Units In Package 2	9
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	9.824 kg

# **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance



#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information