Product datasheet

Specifications





circuit breaker ComPact NSXm B (25 kA at 415 VAC), 4P 3d, 63 A rating TMD trip unit, compression lugs and busbar connectors

LV426265

(!) Discontinued on: 13 Nov 2022

! End-of-service on: 26 Oct 2023

① Discontinued

Main

| Range | ComPact |
|---|--|
| Product Name | ComPact NSXm |
| Range Of Product | ComPact NSXm |
| Device Short Name | NSXm 63B |
| Product Or Component Type | Circuit breaker |
| Device Application | Protection Distribution |
| Number Of Poles | 4P |
| Protected Poles Description | 3D |
| Neutral Position | Left |
| [In] Rated Current | 63 A at 40 °C |
| [Ue] Rated Operational Voltage | 690 V AC 50/60 Hz |
| Network Type | AC |
| Network Frequency | 50/60 Hz |
| Suitability For Isolation | Yes conforming to EN/IEC 60947-2 |
| Utilisation Category | Category A |
| [Icu] Rated Ultimate Short-Circuit Breaking Capacity | 50 kA Icu at 220240 V AC 50/60 Hz conforming to IEC 60947-2 25 kA Icu at 380415 V AC 50/60 Hz conforming to IEC 60947-2 20 kA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2 10 kA Icu at 500 V AC 50/60 Hz conforming to IEC 60947-2 |
| Performance Level | B 25 kA 415 V AC |
| Trip Unit Name | TM-D |
| Trip Unit Technology | Thermal-magnetic |
| Trip Unit Protection Functions | LI |
| Control Type | Toggle |
| Circuit Breaker Mounting Mode | By screws Clip-on |

Complementary

| [Ui] Rated Insulation Voltage | 800 V AC 50/60 Hz |
|---|-------------------|
| [Uimp] Rated Impulse Withstand Voltage | 8 kV |

| [Ics] Rated Service Short-Circuit Breaking Capacity | 50 kA at 220240 V AC 50/60 Hz conforming to IEC 60947-2 25 kA at 380415 V AC 50/60 Hz conforming to IEC 60947-2 20 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2 10 kA at 500 V AC 50/60 Hz conforming to IEC 60947-2 |
|--|--|
| Mechanical Durability | 20000 cycles |
| Electrical Durability | 10000 cycles at 440 V In 20000 cycles at 440 V In/2 5000 cycles at 690 V In 10000 cycles at 690 V In/2 |
| Mounting Support | Plate DIN rail |
| Connection Terminals | compression lug/busbar |
| Connection Pitch | 35 mm with spreaders 27 mm without spreaders |
| 9 Mm Pitches | 12 module |
| Protection Type | L : for overload protection (thermal) I : for short-circuit protection (magnetic) |
| Trip Unit Rating | 63 A at 40 °C |
| Long-Time Pick-Up Adjustment Type Ir (Thermal Protection) | Adjustable |
| [Ir] Long-Time Protection Pick-Up Adjustment Range | 0.71 x ln |
| Long-Time Protection Delay Adjustment Type Tr | Fixed |
| [Im] Magnetic Protection Pick-Up Range | 800 A |
| Earth-Leakage Protection | Without |
| Number Of Slots For Electrical Auxiliaries | 1 slot(s) for auxiliary switch OF 1 slot(s) for alarm switch SD 1 slot(s) for voltage release MN or MX |
| Width (W) | 108 mm |
| Height (H) | 137 mm |
| Depth (D) | 80 mm |
| Net Weight | 1.42 kg |
| Colour | Grey (RAL 7016) |

Environment

| Standards | EN/IEC 60947 |
|---------------------------------------|---|
| Product Certifications | CCC EAC Marine |
| Pollution Degree | 3 conforming to IEC 60664-1 |
| Ip Degree Of Protection | IP40 conforming to IEC 60529 |
| Ik Degree Of Protection | IK07 conforming to IEC 62262 |
| Ambient Air Temperature For Operation | -2570 °C |
| Ambient Air Temperature For Storage | -5085 °C |
| Relative Humidity | 095 % |
| Operating Altitude | 02000 m without derating 20005000 m with derating |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|---------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 11.7 cm |
| Package 1 Width | 12.5 cm |
| Package 1 Length | 22.0 cm |
| Package 1 Weight | 1.6 kg |

Sustainability Screen Premium*

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|---|
| Eu Rohs Directive | Compliant with Exemptions |
| China Rohs Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile | No need of specific recycling operations |