# **Product datasheet**





! Discontinued

Circuit breaker, ComPact NSX400H, 70kA/415VAC, MicroLogic 5.3A trip unit 400A, 4 poles 4d

LV432702



! Discontinued on: 4 Oct 2021

## Main

| Range   | ComPact  |
|---|--|
| Product Name  | ComPact NSX  |
| Range Of Product  | ComPact NSX400630  |
| Device Short Name                                       | NSX400H  |
| Product Or Component Type                               | Circuit breaker  |
| Device Application                                      | Distribution   |
| Number Of Poles   | 4P   |
| Protected Poles Description                             | 3t + OSN<br>4t<br>3t<br>3t + N/2   |
| Neutral Position  | Left   |
| [In] Rated Current                                      | 400 A at 40 °C   |
| [Ue] Rated Operational Voltage                          | 690 V AC 50/60 Hz  |
| Network Type  | AC   |
| Network Frequency                                       | 50/60 Hz   |
| Suitability For Isolation                               | Yes conforming to EN/IEC 60947-2   |
| Utilisation Category                                    | Category A   |
| [Icu] Rated Ultimate Short-Circuit<br>Breaking Capacity | 85 kA at 240 V AC 50/60 Hz conforming to UL 508 65 kA at 480 V AC 50/60 Hz conforming to UL 508 100 kA Icu at 220/240 V AC 50/60 Hz conforming to IEC 60947-2 35 kA Icu at 525 V AC 50/60 Hz conforming to IEC 60947-2 50 kA Icu at 500 V AC 50/60 Hz conforming to IEC 60947-2 65 kA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2 70 kA Icu at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 20 kA at 600 V AC 50/60 Hz conforming to UL 508 20 kA Icu at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 |
| Performance Level                                       | H 70 kA 415 V AC   |
| Trip Unit Name  | MicroLogic 5.3 A   |
| Trip Unit Technology                                    | Electronic   |
| Trip Unit Protection Functions                          | LSI  |
| Control Type  | Toggle   |
| Circuit Breaker Mounting Mode                           | Fixed  |

### Complementary

| [Ui] Rated Insulation Voltage                              | 800 V AC 50/60 Hz  |
|--|--|
| [Uimp] Rated Impulse Withstand                             | 8 kV   |
| Voltage  |  |
| [Ics] Rated Service Short-Circuit<br>Breaking Capacity     | 11 kA at 525 V AC 50/60 Hz conforming to IEC 60947-2<br>10 kA at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 |
|  | 100 kA at 220/240 V AC 50/60 Hz conforming to IEC 60947-2  |
|  | 50 kA at 500 V AC 50/60 Hz conforming to IEC 60947-2<br>65 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2     |
|  | 70 kA at 380/415 V AC 50/60 Hz conforming to IEC 60947-2   |
| Mechanical Durability                                      | 15000 cycles   |
| Electrical Durability                                      | 3000 cycles at 690 V In  |
|  | 6000 cycles at 690 V In/2<br>6000 cycles at 440 V In   |
|  | 12000 cycles at 440 V In/2   |
| Mounting Support   | Backplate  |
| Upside Connection  | Front  |
| <b>Downside Connection</b>                                 | Front  |
| Connection Pitch   | 45 mm  |
| Protection Type  | L : for overload protection (long time)  |
|  | S : for short time short-circuit protection I : for instantaneous short-circuit protection                       |
| Trip Unit Rating   | 400 A at 40 °C   |
| Long-Time Pick-Up Adjustment Type Ir (Thermal Protection)  | Adjustable   |
| [Ir] Long-Time Protection Pick-Up                          | 160400 A   |
| Adjustment Range  Long-Time Protection Delay               | Adjustable   |
| Adjustment Type Tr   | ·  |
| [Tr] Long-Time Protection Delay<br>Adjustment Range        | 15400 s at 1.5 x lr<br>0.3511 s at 7.2 x lr  |
|  | 0.516 s at 6 x lr  |
| Thermal Memory   | 20 minutes before and after tripping   |
| Short-Time Protection Pick-Up<br>Adjustment Type Isd       | Adjustable   |
| [Isd] Short-Time Protection Pick-<br>Up Adjustment Range   | 1.510 x lr   |
| Short-Time Protection Delay<br>Adjustment Type Tsd         | Adjustable   |
| [Tsd] Short-Time Protection Delay<br>Adjustment Range      | 00.4 s   |
| Instantaneous Protection Pick-Up<br>Adjustment Type Ii     | Adjustable   |
| [li] Instantaneous Protection Pick-<br>Up Adjustment Range | 1.512 x ln   |
| Earth-Leakage Protection                                   | Without  |
| Neutral Protection Settings                                | 0.5 x lr (3t + N/2)  |
|  | 1 x lr (4t)<br>1.6 x lr (3t + OSN)   |
|  | No protection (3t)   |
| Zone Selective Interlocking Zsi                            | With   |
| Number Of Slots For Electrical Auxiliaries                 | 6 slot(s)  |
| Local Signalling   | Flashing LED (green) for ready to operate  |
|  | LED 105 % Ir (red) for overload<br>LED 90 % Ir (orange) for overload   |
| Diamles Toma   |  |
| Display Type   | LCD display  |
| Type Of Measurement  | Ammeter  |

| Communication Of Data | Instantaneous and demand values Protection and alarm settings Power quality Time-stamped histories and event tables Demand current and power Energy metering Maximeters/minimeters Maintenance indicators |
|-----------------------|---|
| Width (W)             | 185 mm  |
| Height (H)            | 255 mm  |
| Depth (D)             | 110 mm  |
| Net Weight            | 7.9 kg  |

### **Environment**

| Standards                             | EN/IEC 60947   |
|---------------------------------------|--|
| Product Certifications                | CCC<br>EAC<br>Marine                                   |
| Overvoltage Category                  | Class II   |
| Electrical Shock Protection Class     | Class II   |
| Pollution Degree                      | 3 conforming to IEC 60664-1                            |
| Ip Degree Of Protection               | IP40 conforming to IEC 60529                           |
| Ik Degree Of Protection               | IK07 conforming to IEC 62262                           |
| Ambient Air Temperature For Operation | -2570 °C   |
| Ambient Air Temperature For Storage   | -4085 °C   |
| Relative Humidity                     | 095 %  |
| Operating Altitude                    | 02000 m without derating<br>2000 m5000 m with derating |

### **Packing Units**

| Unit Type Of Package 1       | PCE      |
|------------------------------|----------|
| Number Of Units In Package 1 | 1        |
| Package 1 Height             | 10 cm    |
| Package 1 Width              | 10 cm    |
| Package 1 Length             | 10.01 cm |
| Package 1 Weight             | 7.418 kg |

### **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



RoHS/REACh

### Well-being performance



Mercury Free



Rohs Exemption Information

Yes

#### **Certifications & Standards**

| Eu Rohs Directive     | Compliant  |
|-----------------------|--|
|                       | EU RoHS Declaration  |
| China Rohs Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |