Product datasheet

Specification





Circuit breaker frame, MasterPact MTZ1 12H3 drawout for MicroLogic X, 1250A, 66kA/415VAC (Icu), 4P

LV846460

Main

Range	MasterPacT
Product Name	MasterPact MTZ1
Device Short Name	MTZ1 12 H3
Product Or Component Type	Circuit breaker
Device Application	Power distribution protection
Poles Description	4P
Neutral Position	Left
Control Unit	Without control unit
Product Compatibility	control unit MicroLogic 2.0 X control unit MicroLogic 5.0 X control unit MicroLogic 6.0 X control unit MicroLogic 7.0 X control unit MicroLogic 2.0 Xi control unit MicroLogic 5.0 Xi control unit MicroLogic 6.0 Xi control unit MicroLogic 6.0 Xi control unit MicroLogic 7.0 Xi
[In] Rated Current	1250 A at 40 °C
Performance Type	H3 66 kA 415 V AC
[Ue] Rated Operational Voltage	690 V AC 50/60 Hz
Suitability For Isolation	Yes conforming to EN/IEC 60947-2
Selectivity Category	Category B
Control Type	Push-button
Mounting Mode	Drawout

Complementary

[Icu] Rated Ultimate Short-Circuit Breaking Capacity	66 kA at 220/415 V AC 50/60 Hz 66 kA at 440 V AC 50/60 Hz
[Ics] Rated Service Breaking Capacity	50 kA at 440 V AC 50/60 Hz 50 kA at 220/415 V AC 50/60 Hz
[Icw] Rated Short-Time Withstand Current	30 kA 3 s 50 kA 1 s 50 kA 0.5 s
[Icm] Rated Short-Circuit Making Capacity	145 kA 220/415 V AC at 50/60 Hz 145 kA 440 V AC at 50/60 Hz
Integrated Instantaneous Protection (Din In Ka Peak)	94.5115.5 kA

23 Apr 2024 Life Is On Schneider

Sensor Rating	630 A
	800 A
	1000 A
	1250 A
	1230 A
[Ui] Rated Insulation Voltage	1000 V AC 50/60 Hz
[Uimp] Rated Impulse Withstand	12 kV
Voltage	
Power Dissipation In W	250 W
Maximum Breaking Time	25 ms
Maximum Closing Response Time	50 ms
Mounting Support	Rails
	Base plate
Upside Connection	Front
	Rear
Downside Connection	Front
Downside Connection	Rear
	Real
Connection Pitch	70 mm
Mechanical Durability	10000 cycles with periodic preventive maintenance
Electrical Durability	6000 cycles 440 V AC 50/60 Hz at In conforming to EN/IEC 60947-2
•	AC-23A: 6000 cycles 440 V AC 50/60 Hz at In conforming to EN/IEC 60947-3
	AC-3: 6000 cycles 440 V AC 50/60 Hz at In conforming to EN/IEC 60947-3
	,
Height	Drawout circuit breaker with chassis: 322 mm
	Drawout circuit breaker without chassis: 259.5 mm
Width	Descript size of hypothese with shoosies 250 mass
widii	Drawout circuit breaker with chassis: 358 mm
	Drawout circuit breaker without chassis: 306.5 mm
Depth	Drawout circuit breaker with chassis: 291 mm
	Drawout circuit breaker without chassis: 207.5 mm
Net Weight	39 kg
Standards	EN/IEC 60947-1
	EN/IEC 60947-2
	EN/IEC 60947-2 Annex H
	IEC 61557-12
Product Certifications	CE
	IECEE CB Scheme

Environment

Ip Degree Of Protection	IP30 conforming to EN 60529
Pollution Degree	3 conforming to IEC 60947-1
Ambient Air Temperature For Operation	-2570 °C
Ambient Air Temperature For Storage	-4085 °C
Operating Altitude	02000 m without derating 20005000 m with derating

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	40.0 cm
Package 1 Width	30.0 cm
Package 1 Length	40.0 cm
Package 1 Weight	15.0 kg



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

	Mercury Free	
②	Rohs Exemption Information	Yes
⊘	Pvc Free	

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information