Product datasheet

Specifications





Linergy, Screw Terminal, Protective Earth, 2 Points, 2,5mm², Green-Yellow

NSYTRV22PE

Main

Range	Linergy
Product Name	Linergy TR
Product Or Component Type	Terminal block
Device Short Name	TRV
Terminal Block Type	Protective earth
Terminal Block Level	1
Mounting Mode	Clip-on
Nominal Cross Section	2.5 mm ²
Length	47.7 mm
Colour	Green-yellow
Quantity Per Set	Set of 50

Complementary

· · · · · · · · · · · · · · · · · ·	
Width	5.2 mm
Height	47.5 mm
Connections - Terminals	1 x screw terminal: upstream 1 x screw terminal: downstream
Number Of Connections	2
Connection Position	Sideways
Number Of Measurement Input	2
Cable Cross Section	0.144 mm ² , solid 0.22.5 mm ² , flexible with cable end 0.144 mm ² , flexible without cable end
Tightening Torque	0.50.6 N.m
Wire Stripping Length	9 mm
ТооІ Туре	Connection: screwdriver Disconnection: screwdriver
Material	Polyamide 6/6: insulating case
Dielectric Loss	0.01 at 1 MHz conforming to IEC 60250 0.01 at 1 MHz conforming to VDE 0303-T4
Dielectric Constant	3.7 at 1 MHz
Resistivity	10000 MΩ.m conforming to IEC 60093 10000 MΩ.m conforming to VDE 0303-T30
Surface Resistance	1000 G Ω conforming to IEC 60093 1000 G Ω conforming to VDE 0303-T30

Creep Resistance	500 CTI (> 400 kB) conforming to IEC 60093
	500 CTI (> 400 kB) conforming to VDE 0303-T30
Flame Retardance	V0, thickness0.8 mm conforming to UL 94
Net Weight	11.58 g
Range Compatibility	Prisma G
	Prisma P
	Prisma PH
	Prisma Pack
	Spacial
	Kaedra
	Pragma
	TeSys
Product Compatibility	Spacial enclosures

Environment

Product Certifications	GL		
	CSA		
	cURus		
	LR DNV IEC-Ex		
			VDE
			ATEX
	EAC		
	Dielectric Strength	1000 V conforming to IEC 60243-1	
	Ambient Air Temperature For Operation	-40130 °C conforming to IEC 60216-1 -40130 °C conforming to VDE 0304-T21	

Packing Units

PCE
1
0.700 cm
4.800 cm
5.000 cm
11.000 g
BB1
50
5.000 cm
6.800 cm
25.200 cm
593.000 g
\$03
900
30.000 cm
30.000 cm
40.000 cm
11.160 kg

Contractual warranty

Warranty

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Mercury Free
Rohs Exemption Information Yes
Halogen Free Plastic Parts Product

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations