Product data sheet

Specifications

SQUARE D



Transformer, dry type, 225kVA, 3 phase, 480V delta primary, 208Y/ 120V secondary, 25D, 115C rise, Cu

EE225T3HFCU

(!) Discontinued on: Oct 11, 2022

Main

mann	
Product	Energy Efficient Transformer
Enclosure Code	25D
Enclosure Type	NEMA 2
Insulation Temperature	428 °F (220 °C)
Phase	3 phases
Primary Voltage	480 V delta
Power Rating	225 kVA
Secondary Voltage	208Y/120 V
Full Capacity Taps	6 2.5 % 2+ 4-
Temperature Rise	115 °C
Winding Material	Copper

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	52.99 in (134.6 cm)
Package 1 Width	30.51 in (77.5 cm)
Package 1 Length	37.01 in (94.0 cm)
Package 1 Weight	1313.00 lb(US) (595.567 kg)

Contractual warranty

Warranty

18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency

Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Environmental Disclosure	Product Environmental Profile