

Product data sheet

Specifications

SQUARE D



Transformer, dry type, 500kVA, 3 phase, 208V delta primary, 480Y/277V secondary, 30D, 150C rise

EE500T212H

Main

| | |
|------------------------|------------------------------|
| Product | Energy Efficient Transformer |
| Enclosure Code | 30D |
| Enclosure Type | NEMA 2 |
| Insulation Temperature | 428 °F (220 °C) |
| Phase | 3 phases |
| Primary Voltage | 208 V delta |
| Power Rating | 500 kVA |
| Secondary Voltage | 480Y/277 V |
| Full Capacity Taps | 3 5 % 1+ 2- |
| Temperature Rise | 150 °C |
| Winding Material | Aluminium |

Packing Units

| | |
|------------------------------|-----|
| Unit Type Of Package 1 | PCE |
| Number Of Units In Package 1 | 1 |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Transparency

Eu Rohs Directive

Pro-active compliance (Product out of EU RoHS legal scope)

[EU RoHS Declaration](#)

Environmental Disclosure

[Product Environmental Profile](#)