Product data sheet

Specifications





PowerLogic HU250 empty box for modem connector protection

EMS59150

Main

Range Of Product	PowerLogic T300
Device Short Name	HU250-EB
Product Or Component Type	Empty modem box

Environment

Ik Degree Of Protection	IK07 conforming to IEC 62262
Relative Humidity	95 % conforming to IEC 60068-2-30
Ambient Air Temperature For Operation	-40185 °F (-4085 °C)
Ambient Air Temperature For Storage	-40185 °F (-4085 °C)
Fire Resistance	1562 °F (850 °C)
Operating Altitude	2000 m
Product Certifications	CE
Height	1.18 in (30 mm)
Width	4.53 in (115 mm)
Depth	5.24 in (133 mm)
Net Weight	0.23 lb(US) (0.105 kg)

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	1.14 in (2.9 cm)
Package 1 Width	4.49 in (11.4 cm)
Package 1 Length	5.24 in (13.3 cm)
Package 1 Weight	2.47 oz (70.0 g)
Unit Type Of Package 2	S02
Number Of Units In Package 2	24
Package 2 Height	5.91 in (15.0 cm)
Package 2 Width	11.81 in (30.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	4.25 lb(US) (1.929 kg)

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance



Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information