Product data sheet





Terminal block, Linergy TR, blue, 6mm2, passthrough, 2 points, set of 10

NSYTRV62BL

Main

Range	Linergy	
Product Name	Linergy TR	
Product Or Component Type	Terminal block	
Device Short Name	TRV	
Accessory / Separate Part Category	Connection accessory	
Terminal Block Type	Passthrough	
Terminal Block Level	1	
Mounting Mode	Clip-on	
Nominal Cross Section	0.01 in² (6 mm²)	
Length	1.88 in (47.7 mm)	
Colour	Blue	
Quantity Per Set	Set of 50	

Complementary

•	
Width	0.32 in (8.2 mm)
Height	1.87 in (47.5 mm)
Connections - Terminals	1 x screw terminal upstream M4) 1 x screw terminal downstream M4)
Number Of Connections	2
Connection Position	Sideways
Number Of Measurement Input	2
Cable Cross Section	0.000.02 in² (0.210 mm²), solid with cable end 0.000.01 in² (0.26 mm²), flexible with cable end 0.000.02 in² (0.210 mm²), solid without cable end 0.000.02 in² (0.210 mm²), flexible without cable end
Tightening Torque	13.2815.93 lbf.in (1.51.8 N.m)
Wire Stripping Length	0.39 in (10 mm)
Tool Type	Connection screwdriver Disconnection screwdriver
[Ue] Rated Operational Voltage	1000 V EN/IEC 60947-7-1 600 V CSA 690 V ATEX Exe II Ex II 2 GD 600 V cURus

Life Is On Schneider Apr 25, 2024

[In] Rated Current	41 A EN/IEC 60947-7-1
	50 A cURus
	50 A CSA
	40 A ATEX Exe II Ex II 2 GD
Material	Polyamide 6/6: insulating case
	Copper alloy: connector and screw
	Copper alloy: commoning link
	Chromium-nickel steel: spring
Dielectric Loss	0.01 at 1 MHz IEC 60250
	0.01 at 1 MHz VDE 0303-T4
Dielectric Constant	3.7 at 1 MHz
Resistivity	10000 MΩ.m IEC 60093
	10000 MΩ.m VDE 0303-T30
Surface Resistance	1000 GΩ IEC 60093
	1000 GΩ VDE 0303-T30
Creep Resistance	500 CTI (> 400 kB) IEC 60093
	500 CTI (> 400 kB) VDE 0303-T30
Flame Retardance	V0 0.03 in (0.8 mm) UL 94
Net Weight	0.49 oz (13.95 g)
Range Compatibility	Prisma G
	Prisma P
	Prisma PH
	Prisma Pack
	Spacial
	Kaedra
	Pragma
	TeSys
Product Compatibility	Spacial enclosures
Environment	
Product Certifications	VDE
	EAC

Product Certifications	VDE EAC GL IEC-Ex LR DNV CSA ATEX cURus	
Dielectric Strength	1000 V IEC 60243-1	
Ambient Air Temperature For Operation	-40266 °F (-40130 °C) IEC 60216-1 -40266 °F (-40130 °C) VDE 0304-T21	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	2.17 in (5.5 cm)
Package 1 Width	3.94 in (10.0 cm)
Package 1 Length	10.24 in (26.0 cm)
Package 1 Weight	0.46 oz (13.0 g)
Unit Type Of Package 2	BB1
Number Of Units In Package 2	50
Package 2 Height	2.17 in (5.5 cm)
Package 2 Width	3.94 in (10.0 cm)

Package 2 Length	10.24 in (26.0 cm)
Package 2 Weight	25.33 oz (718.0 g)
Unit Type Of Package 3	S03
Number Of Units In Package 3	750
Package 3 Height	11.81 in (30.0 cm)
Package 3 Width	11.81 in (30.0 cm)
Package 3 Length	15.75 in (40.0 cm)
Package 3 Weight	24.86 lb(US) (11.277 kg)

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations