# **Product datasheet**

Specification





# Motor circuit breaker, TeSys GV2, 3P, 13-18 A, thermal magnetic, screw clamp terminals

GV2RT20

#### Main

Range	TeSys Deca
Product Name	TeSys GV2 TeSys Deca
Product Or Component Type	Motor circuit breaker
Device Short Name	GV2RT
Device Application	Motor protection Transformer
Trip Unit Technology	Thermal-magnetic

#### Complementary

Complementary	
Poles Description	3P
Network Type	AC
Utilisation Category	Category A conforming to IEC 60947-2
	AC-3 conforming to IEC 60947-4-1
	AC-3e conforming to IEC 60947-4-1
Network Frequency	50/60 Hz conforming to IEC 60947-4-1
Fixing Mode	35 mm symmetrical DIN rail: clipped
	Panel: screwed (with adaptor plate)
Motor Power Kw	4 kW at 220/230 V AC 50/60 Hz motor protection high peak current
	7.5 kW at 400/415 V AC 50/60 Hz motor protection high peak current
	7.5 kW at 440 V AC 50/60 Hz motor protection high peak current
	9 kW at 440 V AC 50/60 Hz motor protection high peak current
	9 kW at 500 V AC 50/60 Hz motor protection high peak current
	15 kW at 690 V AC 50/60 Hz motor protection high peak current
	5 kW at 230/240 V AC 50/60 Hz transformer protection
	6.3 kW at 230/240 V AC 50/60 Hz transformer protection
	10 kW at 400/415 V AC 50/60 Hz transformer protection
	10 kW at 440 V AC 50/60 Hz transformer protection
	10 kW at 500 V AC 50/60 Hz transformer protection
	•
	12.5 kW at 500 V AC 50/60 Hz transformer protection
	10 kW at 690 V AC 50/60 Hz transformer protection
Breaking Capacity	100 kA Icu at 220/230 V AC 50/60 Hz conforming to IEC 60947-2
	15 kA Icu at 400/415 V AC 50/60 Hz conforming to IEC 60947-2
	8 kA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2
	6 kA Icu at 500 V AC 50/60 Hz conforming to IEC 60947-2
	3 kA Icu at 690 V AC 50/60 Hz conforming to IEC 60947-2
Control Type	Toggle
[In] Rated Current	18 A
Thermal Protection Adjustment Range	1318 A conforming to IEC 60947-4-1
Magnetic Tripping Current	400 A
[Ith] Conventional Free Air Thermal Current	18 A conforming to IEC 60947-4-1

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

[Ue] Rated Operational Voltage	690 V AC 50/60 Hz conforming to IEC 60947-2
[Ui] Rated Insulation Voltage	690 V AC 50/60 Hz conforming to IEC 60947-2
[Uimp] Rated Impulse Withstand Voltage	6 kV conforming to IEC 60947-2
Suitability For Isolation	Yes conforming to IEC 60947-1 § 7-1-6
Power Dissipation Per Pole	2.5 W
Mechanical Durability	100000 cycles
Electrical Durability	100000 cycles for AC-3 at 415 V In 100000 cycles for AC-3e at 415 V In
Rated Duty	Continuous conforming to IEC 60947-4-1
Tightening Torque	1.7 N.m - on screw clamp terminal
Width	45 mm
Height	89 mm
Depth	78.5 mm

#### **Environment**

Standards	EN/IEC 60947-2
	EN/IEC 60947-4-1
Product Certifications	CCC
	UL
	CSA
	EAC
	LROS (Lloyds register of shipping)
	BV
	UKCA
Ik Degree Of Protection	IK04
Ip Degree Of Protection	IP20 conforming to IEC 60529
Climatic Withstand	conforming to IACS E10
Ambient Air Temperature For Storage	-4080 °C
Fire Resistance	960 °C conforming to IEC 60695-2-11
Ambient Air Temperature For Operation	-2060 °C
Mechanical Robustness	Shocks: 30 Gn for 11 ms
	Vibrations: 5 Gn, 5150 Hz
Operating Altitude	2000 m

# **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	9.300 cm
Package 1 Width	4.800 cm
Package 1 Length	8.500 cm
Package 1 Weight	293.000 g
Unit Type Of Package 2	S02
Number Of Units In Package 2	24
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm

Package 2 Length	40.000 cm
Package 2 Weight	7.220 kg
Unit Type Of Package 3	P06
Number Of Units In Package 3	384
Package 3 Height	75.000 cm
Package 3 Width	60.000 cm
Package 3 Length	80.000 cm
Package 3 Weight	128.292 kg

## **Contractual warranty**

Warranty 18 months

## Sustainability Green Premium

**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance



Mercury Free



Rohs Exemption Information

Yes


#### **Certifications & Standards**


Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information

#### **Dimensions Drawings**

#### **GV2RT**


#### **Dimensions**







X1: Electrical clearance = 40 mm for Ue < 690 V **Mounting** 

Mounting of external operator GV2AP03











c = 80 on AM1 DP200 (35 x 7.5) c = 88 on AM1 DE200, ED200 (35 x 15) On panel with adapter plate GV2AF02




On pre-slotted plate AM1 PA



On rails DZ5 MB

## **Product datasheet**

#### **GV2RT20**



#### Connections and Schema

GV2ME•• and GV2RT

