Product datasheet

Specification





! Discontinued

circuit breaker ComPact NSX160N, 50 kA at 415 VAC, MicroLogic 2.2 trip unit 160 A, 4 poles 4d

LV430785

- ! Discontinued on: Feb 28, 2024
- ! To be end-of-service on: Sep 3, 2026

Main

| Range | ComPact |
|---|---|
| Product Name | ComPact NSX |
| Range Of Product | ComPact NSX100250 |
| Device Short Name | NSX160N |
| Product Or Component Type | Circuit breaker |
| Device Application | Distribution |
| Number Of Poles | 4P |
| Protected Poles Description | 3t + N/2 4t 3t |
| Neutral Position | Left |
| [In] Rated Current | 160 A at 40 °C |
| [Ue] Rated Operational Voltage | 690 V AC 50/60 Hz |
| Network Type | AC |
| Network Frequency | 50/60 Hz |
| Suitability For Isolation | Yes conforming to EN/IEC 60947-2 |
| Utilisation Category | Category A |
| [Icu] Rated Ultimate Short-Circuit Breaking Capacity | 10 kA at 600 V AC 50/60 Hz conforming to UL 508 85 kA at 240 V AC 50/60 Hz conforming to UL 508 10 kA Icu at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 35 kA Icu at 525 V AC 50/60 Hz conforming to IEC 60947-2 50 kA at 480 V AC 50/60 Hz conforming to UL 508 36 kA Icu at 500 V AC 50/60 Hz conforming to IEC 60947-2 50 kA Icu at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 50 kA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2 90 kA Icu at 220/240 V AC 50/60 Hz conforming to IEC 60947-2 |
| Performance Level | N 50 kA 415 V AC |
| Trip Unit Name | MicroLogic 2.2 |
| Trip Unit Technology | Electronic |
| Trip Unit Protection Functions | LSol |
| Control Type | Toggle |
| Circuit Breaker Mounting Mode | Fixed |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.



Complementary

| Complementary | |
|--|--|
| [Ui] Rated Insulation Voltage | 800 V AC 50/60 Hz |
| [Uimp] Rated Impulse Withstand Voltage | 8 kV |
| [lcs] Rated Service Short-Circuit Breaking Capacity | 10 kA at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 35 kA at 525 V AC 50/60 Hz conforming to IEC 60947-2 36 kA at 500 V AC 50/60 Hz conforming to IEC 60947-2 50 kA at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 50 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2 90 kA at 220/240 V AC 50/60 Hz conforming to IEC 60947-2 |
| Mechanical Durability | 40000 cycles |
| Electrical Durability | 7500 cycles at 690 V In 15000 cycles at 690 V In/2 20000 cycles at 440 V In 40000 cycles at 440 V In/2 |
| Mounting Support | Backplate |
| Upside Connection | Front |
| Downside Connection | Front |
| Connection Pitch | 35 mm |
| Protection Type | L : for overload protection (long time) So : for short time short-circuit protection with fixed delay I : for instantaneous short-circuit protection |
| Trip Unit Rating | 160 A at 40 °C |
| Long-Time Pick-Up Adjustment Type Ir (Thermal Protection) | Adjustable 9 settings |
| [Ir] Long-Time Protection Pick-Up Adjustment Range | 63160 A |
| Long-Time Protection Delay Adjustment Type Tr | Fixed |
| [Tr] Long-Time Protection Delay Adjustment Range | 11 s at 7.2 x lr 16 s at 6 x lr 400 s at 1.5 x lr |
| Thermal Memory | 20 minutes before and after tripping |
| Short-Time Protection Pick-Up Adjustment Type Isd | Adjustable 9 settings |
| [Isd] Short-Time Protection Pick- Up Adjustment Range | 1.510 x lr |
| Short-Time Protection Delay Adjustment Type Tsd | Fixed |
| Instantaneous Protection Pick-Up Adjustment Type Ii | Fixed |
| [li] Instantaneous Protection Pick- Up Adjustment Range | 2400 A |
| Earth-Leakage Protection | Without |
| Neutral Protection Settings | 0.5 x lr (3t + N/2) 1 x lr (4t) No protection (3t) |
| Zone Selective Interlocking Zsi | Without |
| Number Of Slots For Electrical Auxiliaries | 5 slot(s) |
| Local Signalling | Flashing LED (green) for ready to operate LED 105 % Ir (red) for overload LED 90 % Ir (orange) for overload |
| Width (W) | 140 mm |
| Height (H) | 161 mm |
| Depth (D) | 86 mm |
| Net Weight | 2.6 kg |

Environment

| Standards | EN/IEC 60947 |
|---------------------------------------|--|
| Product Certifications | CCC EAC Marine |
| Overvoltage Category | Class II |
| Electrical Shock Protection Class | Class II |
| Pollution Degree | 3 conforming to IEC 60664-1 |
| Ip Degree Of Protection | IP40 conforming to IEC 60529 |
| Ik Degree Of Protection | IK07 conforming to IEC 62262 |
| Ambient Air Temperature For Operation | -2570 °C |
| Ambient Air Temperature For Storage | -5085 °C |
| Relative Humidity | 095 % |
| Operating Altitude | 02000 m without derating 2000 m5000 m with derating |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|-----------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 14.0 cm |
| Package 1 Width | 14.6 cm |
| Package 1 Length | 19.0 cm |
| Package 1 Weight | 2.43 kg |
| Unit Type Of Package 2 | S04 |
| Number Of Units In Package 2 | 9 |
| Package 2 Height | 30.0 cm |
| Package 2 Width | 40.0 cm |
| Package 2 Length | 60.0 cm |
| Package 2 Weight | 22.636 kg |

Contractual warranty

| Warranty | 40 |
|-----------|-----------|
| vvarranty | 18 months |

Sustainability Green Premium

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|---|
| Eu Rohs Directive | Compliant with Exemptions |
| China Rohs Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile | End of Life Information |