Product datasheet

Specification





! Discontinued

circuit breaker ComPact NSX250HB1, 75 kA at 690 VAC, MicroLogic 2.2 trip unit 160 A, 4 poles 4d

LV433543

- ! Discontinued on: Sep 30, 2022
- ! End-of-service on: Jun 30, 2023

Main

Range	ComPact
Product Name	ComPact NSX
Range Of Product	ComPact NSX100250
Device Short Name	NSX250HB1
Product Or Component Type	Circuit breaker
Device Application	Distribution
Number Of Poles	4P
Protected Poles Description	3t + N/2 3t 4t
Neutral Position	Left
[In] Rated Current	160 A at 40 °C
[Ue] Rated Operational Voltage	690 V AC 50/60 Hz
Network Type	AC
Network Frequency	50/60 Hz
Suitability For Isolation	Yes conforming to EN/IEC 60947-2
Utilisation Category	Category A
[Icu] Rated Ultimate Short-Circuit Breaking Capacity	85 kA Icu at 500 V AC 50/60 Hz conforming to IEC 60947-2 80 kA Icu at 525 V AC 50/60 Hz conforming to IEC 60947-2 75 kA Icu at 660/690 V AC 50/60 Hz conforming to IEC 60947-2
Performance Level	HB1 75 kA 690 V AC
Trip Unit Name	MicroLogic 2.2
Trip Unit Technology	Electronic
Trip Unit Protection Functions	LSol
Control Type	Toggle
Circuit Breaker Mounting Mode	Fixed

Complementary

[Ui] Rated Insulation Voltage	800 V AC 50/60 Hz
[Uimp] Rated Impulse Withstand Voltage	8 kV

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Apr 19, 2024 Life Is On Schneider

[Ics] Rated Service Short-Circuit Breaking Capacity	85 kA at 500 V AC 50/60 Hz conforming to IEC 60947-2 80 kA at 525 V AC 50/60 Hz conforming to IEC 60947-2 75 kA at 660/690 V AC 50/60 Hz conforming to IEC 60947-2
Mechanical Durability	20000 cycles
Electrical Durability	5000 cycles at 690 V In 10000 cycles at 690 V In/2 10000 cycles at 440 V In 20000 cycles at 440 V In/2
Mounting Support	Backplate
Upside Connection	Front
Downside Connection	Front
Connection Pitch	35 mm
Protection Type	L : for overload protection (long time) So : for short time short-circuit protection with fixed delay I : for instantaneous short-circuit protection
Trip Unit Rating	160 A at 40 °C
Long-Time Pick-Up Adjustment Type Ir (Thermal Protection)	Adjustable 9 settings
[Ir] Long-Time Protection Pick-Up Adjustment Range	63160 A
Long-Time Protection Delay Adjustment Type Tr	Fixed
[Tr] Long-Time Protection Delay Adjustment Range	11 s at 7.2 x lr 16 s at 6 x lr 400 s at 1.5 x lr
Thermal Memory	20 minutes before and after tripping
Thermal memory	3
Short-Time Protection Pick-Up Adjustment Type Isd	Adjustable 9 settings
Short-Time Protection Pick-Up	
Short-Time Protection Pick-Up Adjustment Type Isd [Isd] Short-Time Protection Pick-	Adjustable 9 settings
Short-Time Protection Pick-Up Adjustment Type Isd [Isd] Short-Time Protection Pick- Up Adjustment Range Short-Time Protection Delay	Adjustable 9 settings 1.510 x lr
Short-Time Protection Pick-Up Adjustment Type Isd [Isd] Short-Time Protection Pick-Up Adjustment Range Short-Time Protection Delay Adjustment Type Tsd Instantaneous Protection Pick-Up	Adjustable 9 settings 1.510 x lr Fixed
Short-Time Protection Pick-Up Adjustment Type Isd [Isd] Short-Time Protection Pick-Up Adjustment Range Short-Time Protection Delay Adjustment Type Tsd Instantaneous Protection Pick-Up Adjustment Type Ii [Iii] Instantaneous Protection Pick-Up	Adjustable 9 settings 1.510 x lr Fixed Fixed
Short-Time Protection Pick-Up Adjustment Type Isd [Isd] Short-Time Protection Pick- Up Adjustment Range Short-Time Protection Delay Adjustment Type Tsd Instantaneous Protection Pick-Up Adjustment Type Ii [Ii] Instantaneous Protection Pick- Up Adjustment Range	Adjustable 9 settings 1.510 x Ir Fixed Fixed 2400 A
Short-Time Protection Pick-Up Adjustment Type Isd [Isd] Short-Time Protection Pick-Up Adjustment Range Short-Time Protection Delay Adjustment Type Tsd Instantaneous Protection Pick-Up Adjustment Type Ii [Iii] Instantaneous Protection Pick-Up Adjustment Range Earth-Leakage Protection	Adjustable 9 settings 1.510 x lr Fixed Fixed 2400 A Without 0.5 x lr (3t + N/2) 1 x lr (4t)
Short-Time Protection Pick-Up Adjustment Type Isd [Isd] Short-Time Protection Pick- Up Adjustment Range Short-Time Protection Delay Adjustment Type Tsd Instantaneous Protection Pick-Up Adjustment Type Ii [Ii] Instantaneous Protection Pick- Up Adjustment Range Earth-Leakage Protection Neutral Protection Settings	Adjustable 9 settings 1.510 x lr Fixed Fixed 2400 A Without 0.5 x lr (3t + N/2) 1 x lr (4t) No protection (3t)
Short-Time Protection Pick-Up Adjustment Type Isd [Isd] Short-Time Protection Pick-Up Adjustment Range Short-Time Protection Delay Adjustment Type Tsd Instantaneous Protection Pick-Up Adjustment Type Ii [Ii] Instantaneous Protection Pick-Up Adjustment Range Earth-Leakage Protection Neutral Protection Settings Zone Selective Interlocking Zsi Number Of Slots For Electrical	Adjustable 9 settings 1.510 x lr Fixed Fixed 2400 A Without 0.5 x lr (3t + N/2) 1 x lr (4t) No protection (3t) Without
Short-Time Protection Pick-Up Adjustment Type Isd [Isd] Short-Time Protection Pick-Up Adjustment Range Short-Time Protection Delay Adjustment Type Tsd Instantaneous Protection Pick-Up Adjustment Type Ii [Ii] Instantaneous Protection Pick-Up Adjustment Range Earth-Leakage Protection Neutral Protection Settings Zone Selective Interlocking Zsi Number Of Slots For Electrical Auxiliaries	Adjustable 9 settings 1.510 x Ir Fixed Fixed 2400 A Without 0.5 x Ir (3t + N/2) 1 x Ir (4t) No protection (3t) Without 5 slot(s) Flashing LED (green) for ready to operate LED 105 % Ir (red) for overload
Short-Time Protection Pick-Up Adjustment Type Isd [Isd] Short-Time Protection Pick-Up Adjustment Range Short-Time Protection Delay Adjustment Type Tsd Instantaneous Protection Pick-Up Adjustment Type Ii [Ii] Instantaneous Protection Pick-Up Adjustment Range Earth-Leakage Protection Neutral Protection Settings Zone Selective Interlocking Zsi Number Of Slots For Electrical Auxiliaries Local Signalling	Adjustable 9 settings 1.510 x lr Fixed Fixed 2400 A Without 0.5 x lr (3t + N/2) 1 x lr (4t) No protection (3t) Without 5 slot(s) Flashing LED (green) for ready to operate LED 105 % lr (red) for overload LED 90 % lr (orange) for overload
Short-Time Protection Pick-Up Adjustment Type Isd [Isd] Short-Time Protection Pick-Up Adjustment Range Short-Time Protection Delay Adjustment Type Tsd Instantaneous Protection Pick-Up Adjustment Type Ii [Ii] Instantaneous Protection Pick-Up Adjustment Range Earth-Leakage Protection Neutral Protection Settings Zone Selective Interlocking Zsi Number Of Slots For Electrical Auxiliaries Local Signalling Width (W)	Adjustable 9 settings 1.510 x Ir Fixed Fixed 2400 A Without 0.5 x Ir (3t + N/2) 1 x Ir (4t) No protection (3t) Without 5 slot(s) Flashing LED (green) for ready to operate LED 105 % Ir (red) for overload LED 90 % Ir (orange) for overload 140 mm

Environment

Standards	EN/IEC 60947
Product Certifications	EAC CCC
	Marine

Overvoltage Category	Class II
Electrical Shock Protection Class	Class II
Pollution Degree	3 conforming to IEC 60664-1
Ip Degree Of Protection	IP40 conforming to IEC 60529
Ik Degree Of Protection	IK07 conforming to IEC 62262
Ambient Air Temperature For Operation	-2570 °C
Ambient Air Temperature For Storage	-5085 °C
Relative Humidity	095 %
Operating Altitude	02000 m without derating 2000 m5000 m with derating

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	13.5 cm
Package 1 Width	14.1 cm
Package 1 Length	19.2 cm
Package 1 Weight	2.63 kg

Contractual warranty

Warranty 18 months

Sustainability Screen Premium

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information