Product datasheet

Specifications

Isolation module - for MX1/XF communicating coils

LV850056

Main

Range	MasterPact
Device Short Name	K70 K60 K80
Product Or Component Type	Isolating block
Device Application	Coil protection
Range Compatibility	Masterpact MX com coil Masterpact XF com coil

Complementary

Control Type	Communicating
Mounting Location	Control enclosure
Product Destination	Control unit
Localisation On Device	Behind control unit
[Uc] Control Circuit Voltage	480 V AC

Environment

Ambient Air Temperature For Operation	-35…70 °C
Ambient Air Temperature For Storage	-40…85 °C

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.0 cm
Package 1 Width	5.0 cm
Package 1 Length	6.0 cm
Package 1 Weight	20.0 g
Unit Type Of Package 2	BB1
Number Of Units In Package 2	16
Package 2 Height	9.0 cm
Package 2 Width	13.0 cm
Package 2 Length	18.0 cm
Package 2 Weight	320.0 g

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Unit Type Of Package 3	S02
Number Of Units In Package 3	96
Package 3 Height	15.0 cm
Package 3 Width	30.0 cm
Package 3 Length	40.0 cm
Package 3 Weight	2.27 kg

Life Is On | Schneider Electric

Sustainability

Green Premium^{TM} label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO_2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

✅ Mercury Free

✅ Rohs Exemption Information   Yes

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration
	Product out of China RoHS scope. Substance declaration for your information