## **Product datasheet**

Specification





# EasyLogic PM2220 - Power & Energy meter - up to 15th H - LCD - RS485 - class 1

METSEPM2220

#### Main

| EasyLogic        |
|------------------|
| EasyLogic PM2200 |
| PM2220           |
| Power meter      |
|                  |

#### Complementary

| Device Application          | Power monitoring  |
|-----------------------------|---|
| Device Application          | Sub billing   |
|                             |   |
| Power Quality Analysis      | total harmonic distortion                                 |
|                             | up to the 15th harmonic                                   |
| Type Of Measurement         | Apparent power min/max, total                             |
|                             | Active and reactive power min/max, total                  |
|                             | Current min/max, avg                                      |
|                             | Voltage min/max, avg                                      |
|                             | Frequency min/max, avg                                    |
|                             | Total current harmonic distortion THD (I) per phase       |
|                             | Total voltage harmonic distortion THD (U) per phase       |
|                             | Power factor min/max, avg                                 |
|                             | Apparent energy total                                     |
|                             | Active and reactive energy total                          |
| Metering Type               | Active, reactive, apparent energy (signed, four quadrant) |
|                             | Current I, I1, I2, I3                                     |
|                             | Peak demand currents                                      |
|                             | Peak demand power PM, QM, SM                              |
|                             | Unbalance current   |
|                             | Active power P, P1, P2, P3                                |
|                             | Reactive power Q, Q1, Q2, Q3                              |
|                             | Demand power P, Q, S                                      |
|                             | Voltage U, U21, U32, U13, V, V1, V2, V3                   |
|                             | Apparent power S, S1, S2, S3                              |
|                             | Calculated neutral current                                |
| Accuracy Class              | Class 1 active energy conforming to IEC 62053-21          |
|                             | Class 1 reactive energy conforming to IEC 62053-24        |
|                             | Class 5 harmonic distorsion (I THD & U THD)               |
| Measurement Accuracy        | Apparent power +/- 1 %                                    |
|                             | Active energy +/- 1 %                                     |
|                             | Reactive energy +/- 1 %                                   |
|                             | Active power +/- 1 %                                      |
|                             | Voltage +/- 0.5 %   |
|                             | Power factor +/- 0.01                                     |
|                             | Current +/- 0.5 %   |
|                             | Frequency +/- 0.05 %                                      |
| Measurement Current         | 56000 mA  |
| Measurement Voltage         | 35480 V AC 50/60 Hz between phases                        |
|                             | 20277 V AC 50/60 Hz between phase and neutral             |
|                             | 480999000 V AC 50/60 Hz with external VT                  |
| Frequency Measurement Range | 4565 Hz   |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| [Us] Rated Supply Voltage          | 44277 V AC 4565 Hz +/- 10 %<br>44277 V DC +/- 10 %   |
|------------------------------------|--|
| Network Frequency                  | 50 Hz<br>60 Hz   |
| Ride-Through Time                  | 100 ms 120 V AC typical<br>400 ms 230 V AC typical<br>50 ms 125 V DC typical   |
| [In] Rated Current                 | 1 A<br>5 A   |
| Maximum Power Consumption In<br>Va | 6 VA at 277 V AC   |
| Maximum Power Consumption In W     | 3.3 W (power lines (AC)) 2 W at 277 V (power lines (DC))   |
| Input Impedance                    | Current (impedance <= 0.3 mOhm) Voltage (impedance > 5 MOhm)   |
| Tamperproof Of Settings            | Protected by access code   |
| Display Type                       | Backlit LCD  |
| Display Colour                     | Monochrome   |
| Display Resolution                 | 128 x 128 pixels   |
| Demand Intervals                   | Configurable from 1 to 60 min  |
| Information Displayed              | Demand current (past value) Demand power (past value) Demand power (past value) Demand power (present value) Voltage Current Frequency Energy consumption Harmonic distortion Power factor Active power Apparent power Reactive power Unbalanced in % Harmonic amplitude |
| Control Type                       | 4 x button   |
| Local Signalling                   | Red LED: output signal 19999000 pulse/ k_h (kWh, kVAh, kVARh) Green LED: module operation and integrated communication   |
| Number Of Inputs                   | 0  |
| Number Of Outputs                  | 0  |
| Communication Port Protocol        | Modbus RTU at 4800 bps, 9600 bps, 19200 bps, 38.4 Kbps even/odd or none - 2 wires, insulation 2500 V   |
| Communication Port Support         | Screw terminal block: RS485  |
| Data Recording                     | Time stamping Min/max for 8 parameters   |
| Function Available                 | Real time clock  |
| Sampling Rate                      | 64 samples/cycle   |
| Cybersecurity                      | Enable/disable communication ports   |
| Communication Service              | Remote monitoring  |
| Language                           | Spanish French English Russian Portuguese German Chinese   |

| Product Certifications      | CE conforming to IEC 61010-1                     |
|-----------------------------|--|
|                             | CULus conforming to UL 61010-1                   |
|                             | CULus conforming to CSA C22.2 No 61010-1         |
|                             | RCM  |
|                             | EAC  |
|                             | C-Tick   |
| Mounting Mode               | Clip-on  |
| Mounting Position           | Vertical   |
| Mounting Support            | Framework  |
| Provided Equipment          | 1 x installation guide                           |
| Measurement Category        | Category III 480 V                               |
|                             | Category II 480600 V                             |
| Electrical Insulation Class | Double insulation                                |
|                             | Class II   |
| Flame Retardance            | V-0 conforming to UL 94                          |
| Connections - Terminals     | Current transformer: screw connection (bottom) 6 |
|                             | Voltage inputs: screw connection (top) 4         |
| Material                    | Polycarbonate                                    |
| Width                       | 96 mm  |
| Depth                       | 76.09 mm total:                                  |
| - <b>1</b>                  | 61.64 mm embedded:                               |
| Height                      | 96 mm  |
| Net Weight                  | 300 g  |
| Compatibility Code          | PM2220   |
|                             |  |
| Environment                 |  |

| Service Life                          | 7 year(s)   |
|---------------------------------------|---|
| Ip Degree Of Protection               | IP54 front: conforming to IEC 60529<br>IP30 body: conforming to IEC 60529   |
| Relative Humidity                     | 595 % at 50 °C  |
| Pollution Degree                      | 2   |
| Ambient Air Temperature For Operation | -1060 °C  |
| Ambient Air Temperature For Storage   | -2570 °C  |
| Operating Altitude                    | <= 2000 m   |
| Electromagnetic Compatibility         | Electrostatic discharge conforming to IEC 61000-4-2 Radiated radio-frequency electromagnetic field immunity test conforming to IEC 61000-4-3 Electrical fast transient/burst immunity test conforming to IEC 61000-4-4 Surge immunity test conforming to IEC 61000-4-5 Conducted RF disturbances conforming to IEC 61000-4-6 Magnetic field at power frequency conforming to IEC 61000-4-8 Voltage dips and interruptions immunity test conforming to IEC 61000-4-11 Emission tests conforming to FCC part 15 class A |
| Overvoltage Category                  | III   |

### **Packing Units**

| Unit Type Of Package 1       | PCE     |
|------------------------------|---------|
| Number Of Units In Package 1 | 1       |
| Package 1 Height             | 8.9 cm  |
| Package 1 Width              | 12.2 cm |

| Package 1 Length | 11.7 cm |  |
|------------------|---------|--|
| Package 1 Weight | 270 a   |  |



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance



Mercury Free



Rohs Exemption Information

Yes

#### **Certifications & Standards**

| Reach Regulation         | REACh Declaration             |
|--------------------------|-------------------------------|
| Eu Rohs Directive        | Compliant with Exemptions     |
| China Rohs Regulation    | China RoHS declaration        |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile      | End of Life Information       |