Product datasheet

Specifications





module XPSAK - Emergency stop - 120 V AC

XPSAK351144

- (!) To be discontinued on: Sep 4, 2027
- (!) To be end-of-service on: Sep 4, 2033

Main

Mann	
Range Of Product	Preventa Safety automation
Product Or Component Type	Preventa safety module
Safety Module Name	XPSAK
Safety Module Application	For emergency stop, switch, sensing mat/edges or safety light curtain monitoring
Function Of Module	Monitoring of a movable guard associated with 2 switches and automatic start
	Sensing mat and edges monitoring
	Proximity sensor monitoring
	Monitoring of electro-sensitive protection equipment (ESPE)
	Multiple emergency stop monitoring 2-channel wiring
	Monitoring of a movable guard
	Emergency stop with 2 NC contacts monitoring 2-channel wiring
	Emergency stop monitoring 1-channel wiring
Safety Level	Can reach PL e/category 4 conforming to EN/ISO 13849-1
	Can reach SILCL 3 conforming to EN/IEC 62061
Safety Reliability Data	DC > 99 % conforming to EN/ISO 13849-1
	MTTFd = 154.5 years conforming to EN/ISO 13849-1
	PFHd = 7.39E-9 1/h conforming to EN/IEC 62061
Type Of Start	Configurable
Connections - Terminals	Captive screw clamp terminals, 1 x 0.141 x 2.5 \mbox{mm}^2 flexible with cable end, with
	double bezel
	Captive screw clamp terminals, 1 x 0.141 x 2.5 mm ² solid with cable end, with
	double bezel
	Captive screw clamp terminals, 1 x 0.251 x 1.5 mm ² flexible with cable end, with
	double bezel
	Captive screw clamp terminals, 1 x 0.251 x 2.5 mm ² flexible with cable end, with
	double bezel
	Captive screw clamp terminals, 2 x 0.142 x 0.75 mm ² flexible with cable end, with
	double bezel
	Captive screw clamp terminals, 2 x 0.142 x 0.75 mm ² solid with cable end, with
	Captive screw clamp terminals, 2 x 0.142 x 0.75 $\rm mm^2$ solid with cable end, with double bezel
	Captive screw clamp terminals, 2 x 0.142 x 0.75 mm ² solid with cable end, with
	Captive screw clamp terminals, 2 x 0.142 x 0.75 mm ² solid with cable end, with double bezel
	Captive screw clamp terminals, $2 \times 0.142 \times 0.75 \text{ mm}^2$ solid with cable end, with double bezel Captive screw clamp terminals, $2 \times 0.252 \times 1 \text{ mm}^2$ flexible with cable end, with
	Captive screw clamp terminals, 2 x 0.142 x 0.75 mm ² solid with cable end, with double bezel Captive screw clamp terminals, 2 x 0.252 x 1 mm ² flexible with cable end, with double bezel
Output Type	Captive screw clamp terminals, 2 x 0.142 x 0.75 mm ² solid with cable end, with double bezel Captive screw clamp terminals, 2 x 0.252 x 1 mm ² flexible with cable end, with double bezel Captive screw clamp terminals, 2 x 0.52 x 1.5 mm ² flexible with cable end, with
Output Type Number Of Additional Circuits	Captive screw clamp terminals, 2 x 0.142 x 0.75 mm ² solid with cable end, with double bezel Captive screw clamp terminals, 2 x 0.252 x 1 mm ² flexible with cable end, with double bezel Captive screw clamp terminals, 2 x 0.52 x 1.5 mm ² flexible with cable end, with double bezel
	Captive screw clamp terminals, 2 x 0.142 x 0.75 mm ² solid with cable end, with double bezel Captive screw clamp terminals, 2 x 0.252 x 1 mm ² flexible with cable end, with double bezel Captive screw clamp terminals, 2 x 0.52 x 1.5 mm ² flexible with cable end, with double bezel Relay instantaneous opening, 3 NO circuit(s), volt-free

Complementary

Synchronisation Time Between	2 or 4 s depending of wiring (automatic start)
Inputs	Unlimited (manual start)
Supply Frequency	50/60 Hz

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Maximum Power Consumption In Va	6 VA AC
Input Protection Type	Internal, electronic
[Uc] Control Circuit Voltage	24 V DC
Maximum Line Resistance	28 Ohm
Breaking Capacity	180 VA holding AC-15 C300 relay output 1800 VA inrush AC-15 C300 relay output
Breaking Capacity	1.5 A at 24 V (DC-13) time constant: 50 ms for relay output
Output Thermal Current	6 A per relay for relay output
[Ith] Conventional Free Air Thermal Current	18 A
Associated Fuse Rating	4 A gG or gL for relay output conforming to EN/IEC 60947-5-1, DIN VDE 0660 part 200 6 A fast blow for relay output conforming to EN/IEC 60947-5-1, DIN VDE 0660 part 200
Minimum Output Current	10 mA for relay output
Minimum Output Voltage	17 V for relay output
Maximum Response Time On Input Open	40 ms
[Ui] Rated Insulation Voltage	300 V (pollution degree 2) conforming to IEC 60947-5-1 300 V (pollution degree 2) conforming to DIN VDE 0110 part 1
[Uimp] Rated Impulse Withstand Voltage	4 kV overvoltage category III conforming to IEC 60947-5-1 4 kV overvoltage category III conforming to DIN VDE 0110 part 1
Local Signalling	4 LEDs
Current Consumption	30 mA at 24 V AC on power supply
Mounting Support	35 mm symmetrical DIN rail
Net Weight	0.4 kg

Environment

Standards	EN/ISO 13850 EN/IEC 60204-1 EN 1088/ISO 14119 EN/IEC 60947-5-1
Product Certifications	UL TÜV CSA
Ip Degree Of Protection	IP20 (terminals) conforming to EN/IEC 60529 IP40 (enclosure) conforming to EN/IEC 60529
Ambient Air Temperature For Operation	-1055 °C
Ambient Air Temperature For Storage	-2585 °C

Packing Units

J	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	6.5 cm
Package 1 Width	12.5 cm
Package 1 Length	10.5 cm
Package 1 Weight	465.0 g
Unit Type Of Package 2	S02

Number Of Units In Package 2	12
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	6.09 kg

Contractual warranty

Warranty

18 months

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance



Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information

Dimensions Drawings

Dimensions

