Product datasheet

Specifications





Light block for head Ø22, red, integral LED, 24 V AC/DC

ZBVB4

() Discontinued on: Mar 28, 2024

(!) Discontinued

Main

Range Of Product Harmony XB4 Harmony XB5 Product Or Component Type Light block Device Short Name ZBV Sale Per Indivisible Quantity 5 Connections - Terminals Screw clamp terminals, <= 2 x 1.5 mm² with cable end conforming to EN 60947. Screw clamp terminals, >= 1 x 0.22 mm² without cable end conforming to EN 60947-1 Signalling Type Steady Light Source Protected LED Bulb Base Integral LED Light Block Supply Direct Light Source Colour Red [Us] Rated Supply Voltage 24 V AC/DC at 50/60 Hz		
Device Short Name ZBV Sale Per Indivisible Quantity 5 Connections - Terminals Screw clamp terminals, <= 2 x 1.5 mm² with cable end conforming to EN 60947 Screw clamp terminals, >= 1 x 0.22 mm² without cable end conforming to EN 60947-1 Signalling Type Steady Light Source Protected LED Bulb Base Integral LED Light Block Supply Direct Light Source Colour Red	Range Of Product	
Sale Per Indivisible Quantity 5 Connections - Terminals Screw clamp terminals, <= 2 x 1.5 mm² with cable end conforming to EN 60947 Screw clamp terminals, >= 1 x 0.22 mm² without cable end conforming to EN 60947-1 Signalling Type Steady Light Source Protected LED Bulb Base Integral LED Light Block Supply Direct Light Source Colour Red	Product Or Component Type	Light block
Connections - Terminals Screw clamp terminals, <= 2 x 1.5 mm² with cable end conforming to EN 60947	Device Short Name	ZBV
Signalling Type Steady Light Source Protected LED Bulb Base Integral LED Light Block Supply Direct	Sale Per Indivisible Quantity	5
Light Source Protected LED Bulb Base Integral LED Light Block Supply Direct Light Source Colour Red	Connections - Terminals	
Bulb Base Integral LED Light Block Supply Direct Light Source Colour Red	Signalling Type	Steady
Light Block Supply Direct Light Source Colour Red	Light Source	Protected LED
Light Source Colour Red	Bulb Base	Integral LED
	Light Block Supply	Direct
[Us] Rated Supply Voltage 24 V AC/DC at 50/60 Hz	Light Source Colour	Red
	[Us] Rated Supply Voltage	24 V AC/DC at 50/60 Hz

Complementary

<u> </u>		
Net Weight	0.017 kg	
Tightening Torque	0.81.2 N.m conforming to EN 60947-1	
Shape Of Screw Head	Cross compatible with Philips no 1 screwdriver Cross compatible with pozidriv No 1 screwdriver Slotted compatible with flat $Ø$ 4 mm screwdriver Slotted compatible with flat $Ø$ 5.5 mm screwdriver	
Supply Voltage Limits	19.230 V DC 21.626.4 V AC	
Current Consumption	18 mA	
Service Life	100000 h at rated voltage and 25 °C	
Surge Withstand	1 kV conforming to IEC 61000-4-5	
Mounting Of Block	Front mounting	

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Electrical Composition Code	M1
	M2
	M3
	M4
	M5
	M6
	M10
	MF1
	P1
	P2
	PF1
Device Presentation	Basic element

Environment

Protective Treatment	ТН
Ambient Air Temperature For Storage	-4070 °C
Ambient Air Temperature For Operation	-4070 °C
Ip Degree Of Protection	IP20 conforming to IEC 60529
Standards	EN/IEC 60947-5-4 EN/IEC 60947-5-5 UL 508 CSA C22.2 No 14 EN/IEC 60947-5-1 JIS C8201-5-1 EN/IEC 60947-1 JIS C8201-1
Product Certifications	CSA UL listed
Resistance To Fast Transients	2 kV conforming to IEC 61000-4-4
Resistance To Electromagnetic Fields	10 V/m conforming to IEC 61000-4-3
Resistance To Electrostatic Discharge	6 kV on contact (on metal parts) conforming to IEC 61000-4-2 8 kV in free air (in insulating parts) conforming to IEC 61000-4-2
Electromagnetic Emission	Class B conforming to IEC 55011
[Us] Rated Supply Voltage	24 V

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	5.6 cm
Package 1 Width	4.4 cm
Package 1 Length	5.6 cm
Package 1 Weight	9 g
Unit Type Of Package 2	BB1
Number Of Units In Package 2	5
Package 2 Height	5.6 cm
Package 2 Width	4.4 cm
Package 2 Length	5.6 cm
Package 2 Weight	51 g
Unit Type Of Package 3	\$03
Number Of Units In Package 3	800

Package 3 Height	30 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	8.696 kg

Contractual warranty

Warranty

18 months

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance



Rohs Exemption Information Yes

Certifications & Standards


Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information

Product datasheet

Dimensions Drawings

Dimensions

with ZB5AZ009 Fixing Collar



with ZB4BZ009 Fixing Collar

