Product datasheet

Specifications





switch disconnector, Compact INS63, 63A, with red rotary handle and yellow front, 4 poles

28919

① Discontinued

Main

Range	ComPact
Product Name	ComPacT INS
Product Or Component Type	Switch disconnector
Poles Description	4P
Network Type	AC
	DC
Network Frequency	50/60 Hz
[le] Rated Operational Current	AC-22A: 63 A AC 50/60 Hz 220/240 V
	AC-22A: 63 A AC 50/60 Hz 380/415 V 2 poles in series
	AC-22A: 63 A AC 50/60 Hz 440/480 V 4 poles in series
	AC-22A: 63 A AC 50/60 Hz 500 V 4 poles in series
	AC-23A: 40 A AC 50/60 Hz 500 V
	AC-23A: 63 A AC 50/60 Hz 220/240 V
	AC-23A: 63 A AC 50/60 Hz 380/415 V
	AC-23A: 63 A AC 50/60 Hz 440/480 V
	DC-22A: 63 A DC 50/60 Hz 125 V 2 poles in series
	DC-23A: 63 A DC 50/60 Hz 125 V 2 poles in series
	DC-22A: 63 A DC 50/60 Hz 250 V 4 poles in series
	DC-23A: 63 A DC 250 V 4 poles in series
[Ui] Rated Insulation Voltage	690 V AC 50/60 Hz
[Uimp] Rated Impulse Withstand Voltage	8 kV
[Ith] Conventional Free Air Thermal Current	63 A at 60 °C
[Icm] Rated Short-Circuit Making	15 kA switch-disconnector alone 500 V AC at 50/60 Hz
Capacity	75 kA with upstream protection circuit breaker 500 V AC at 50/60 Hz
[Ue] Rated Operational Voltage	500 V AC 50/60 Hz
[De] Nated Operational Voltage	250 V AC 50/80 H2
	250 V DC
Suitability For Isolation	Yes
Contact Position Indicator	Yes
Visible Break	No
Pollution Dograd	2
Pollution Degree	3

Complementary

Control Type	Rotary handle
Handle Colour	Red
Mounting Mode	Fixed
Mounting Support	Plate DIN rail

Upside Connection	Front
Downside Connection	Front
Cable Cross Section	1.550 mm ²
Maximum Power	AC-23: 15 kW at 220/240 V AC 50/60 Hz AC-23: 22 kW at 500/525 V AC 50/60 Hz AC-23: 30 kW at 380/415 V AC 50/60 Hz AC-23: 30 kW at 440 V AC 50/60 Hz
Rated Duty	Uninterrupted
Intermittent Duty Class	Class 120 - 60 %
Enclosure Dimensions For Ithe	190 mm x 115 mm x 55 mm
[Icw] Rated Short-Time Withstand Current	0.067 kA during 20 s conforming to IEC 60947-3 1.73 kA during 3 s conforming to IEC 60947-3 3 kA during 1 s conforming to IEC 60947-3 5.5 kA during 30 s conforming to IEC 60947-3
Mechanical Durability	20000 cycles
Electrical Durability	AC-22A: 1500 cycles 220/240 V AC 50/60 Hz AC-22A: 1500 cycles 380/415 V AC 50/60 Hz 4 poles in series AC-22A: 1500 cycles 440 V AC 50/60 Hz AC-22A: 1500 cycles 500 V AC 50/60 Hz AC-23A: 1500 cycles 220/240 V AC 50/60 Hz AC-23A: 1500 cycles 380/415 V AC 50/60 Hz AC-23A: 1500 cycles 440 V AC 50/60 Hz AC-23A: 1500 cycles 500 V AC 50/60 Hz AC-23A: 1500 cycles 500 V AC 50/60 Hz DC-22A: 1500 cycles 250 V DC 50/60 Hz 4 poles in series DC-23A: 1500 cycles 250 V DC 4 poles in series
Connection Pitch	18 mm
Height	85 mm
Width	90 mm
Depth	62.5 mm
Net Weight	0.6 kg

Environment

Standards	IEC 60947-1 IEC 60947-3	
Product Certifications	CCC KEMA-KEUR	
Ip Degree Of Protection	IP40 conforming to IEC 60529	
Ik Degree Of Protection	IK07 conforming to EN 50102	
Ambient Air Temperature For Operation	-2570 °C	
Ambient Air Temperature For Storage	-5085 °C	

Packing Units

U	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	9.6 cm
Package 1 Width	9.4 cm
Package 1 Length	10.1 cm
Package 1 Weight	649.0 g
Unit Type Of Package 2	S03

Number Of Units In Package 2	18
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	12.09 kg

Contractual warranty

Warranty

18 months

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc

Toxic Heavy Metal Free	
Mercury Free	
Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information