Product datasheet

Specifications





Enclosed DOL starter, TeSys LE, 25A, 380V AC coil, including 1 LC1D, 2 pushbuttons

LE1D25Q7

Main

Range	TeSys	
Product Name	TeSys LE	
Device Short Name	LE1D	
Product Or Component Type	Enclosed DOL starter	
Device Application	Standard	
Utilisation Category	AC-3	
Device Composition	Thermal overload relay ordered separately Contactor	
Control Type	Push-button start green I Push-button stop/reset red O	

Complementary

Motor Power Kw	11 kW at 380/400 V AC 50/60 Hz
	11 kW at 415 V AC 50/60 Hz
	11 kW at 440 V AC 50/60 Hz
	15 kW at 500 V AC 50/60 Hz
	15 kW at 660/690 V AC 50/60 Hz
	5.5 kW at 220/230 V AC 50/60 Hz
[Ith] Conventional Free Air Thermal Current	22 A
[Uc] Control Circuit Voltage	380 V AC 50/60 Hz
Cable Entry Number	2 ISO20 top
	2 ISO25 top
	2 ISO20 bottom
	2 ISO25 bottom
Width	101 mm
Height	201 mm
Depth	153.5 mm
Net Weight	1.015 kg

Environment

Material	Polycarbonate
Ip Degree Of Protection	IP65 conforming to IEC 60529
Ik Degree Of Protection	IK07 conforming to IEC 60529
Standards	IEC 60947-4-1
Ambient Air Temperature For Operation	-540 °C
Environmental Characteristic	Standard environment

23 Apr 2024 Life Is On Schneider

Product Certifications UKCA

Packing Units

•	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	20.500 cm
Package 1 Width	18.500 cm
Package 1 Length	26.000 cm
Package 1 Weight	1.242 kg
Unit Type Of Package 2	P06
Number Of Units In Package 2	22
Package 2 Height	75.000 cm
Package 2 Width	60.000 cm
Package 2 Length	80.000 cm
Package 2 Weight	40.258 kg

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

⊘	Reach Free Of Svhc	
9	Toxic Heavy Metal Free	
②	Mercury Free	
⊘	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information