Product datasheet

Specification





PowerLogic™ ION9000 meter, DIN mount, no display, HW kit

METSEION92030

Main

Range	PowerLogic
Device Short Name	ION92030
Product Or Component Type	Energy and power quality meter
Device Application	Power monitoring WAGES metering Net metering Medium voltage High voltage
Metering Type	Demand current I1, I2, I3, I4, I5 Peak demand currents Demand power P, Q, S Peak demand power PM, QM, SM Calculated active and reactive energy (+/- W.h, +/- VAR.h)

Complementary

<u>Complementary</u>	
Power Quality Analysis	EN 50160 compliance checking conforming to IEEE 519 harmonic limit conforming to IEC 61000-4-30: class A compliance reporting conforming to IEEE 519 compliance reporting waveform capture total demand distortion total harmonic distortion up to the 63rd harmonic up to the 127th harmonic with software disturbance direction detection dip, swell and transient half cycle data acquisition transient detection (20 µs)
Type Of Measurement	Voltage sags and swells Current sags and swells Voltage Current Frequency Active and reactive power total Apparent power total Active and reactive power per phase Apparent power per phase Apparent power per phase Power factor total Power factor total Power factor total Power factor per phase Active and reactive energy Apparent energy Harmonic distorsion (I THD & U THD)
[Us] Rated Supply Voltage	90480 V AC 4566 Hz +/- 10 % 90120 V AC 400 Hz +/- 10 % 110480 V DC +/- 15 %
Network Frequency	50 Hz 60 Hz
Ride-Through Time	100 ms 6 cycles at 60 Hz 120 V AC typical 400 ms 24 cycles at 60 Hz 240 V AC typical 1200 ms 72 cycles at 60 Hz 480 V AC typical

[In] Rated Current	1 A 5 A
Type Of Network	3P + N + E
Power Consumption In Va	38 VA at 480 V AC
Maximum Power Consumption In Va	80 VA at 480 V AC
Display Type	Without display
Sampling Rate	1024 samples/cycle
Measurement Current	0.0120 A
Input Type	Voltage (impedance 5 MOhm) External CT (impedance 0.3 mOhm)5 x
Measurement Voltage	57400 V AC 4269 Hz between phase and neutral 100690 V AC 4269 Hz between phases
Frequency Measurement Range	20450 Hz
Number Of Inputs	8 digital 30 V AC/60 V DC
Measurement Accuracy	Voltage +/- 0.1 % Current +/- 0.1 %
Accuracy Class	Class 0.1S active energy conforming to IEC 62053-22 Class 0.1 active energy conforming to IEC 61557-12 Class 0.1 active energy conforming to ANSI C12.20 Class 0.5S reactive energy conforming to IEC 62053-24 Class 0.1 current conforming to IEC 61557-12 Class 0.1 voltage conforming to IEC 61557-12 Class 0.1 active power conforming to IEC 61557-12 Class 0.5 power factor conforming to IEC 61557-12
Number Of Outputs	4 digital 2 form C relay
Communication Port Protocol	Modbus RTU at 2400115200 bps - 2-wire ION at 2400115200 bps - 2-wire DNP3 at 240015200 bps - 2-wire Modbus TCP at 10/100 Mbit/s ION TCP at 10/100 Mbit/s DNP3 TCP at 10/100 Mbit/s IEC 61850 Ethernet Modbus TCP/IP daisy chain at 10/100 Mbit/s DHCP DNS DLMS
Communication Port Support	RS485 2 removable screw terminal block
Port Ethernet	10/100BASE-TX 2 RJ45
Communication Gateway	Ethernet/serial
Time Synchronisation Protocol	GPS IRIG-B NTP SNTP PTP
Data Recording	Time stamping Min/max of instantaneous values User-definable data logs Continuous logging or snapshot Trending/forecasting Event logs Alarm logs Configuration change Power outage User login/logout Data logs GPS synchronisation Sequence of event recording
Memory Capacity	2 GB

Cybersecurity	Syslog protocol support Robust security logs Port hardening Enable/disable communication ports Hardware metrology lock	
Web Services	Viewing of captured waveform Web page Pass/fail report for IEEE 519 Pass/fail report for EN 50160 ITIC (CBEMA) curve SEMI curve NEMA motor derating curve Alarm notification by e-mail TLS 1.2 Push historical data via mail	
Ethernet Service	DHCP client Device Profile Web Services (DPWS) Rapid Scanning Tree Protocol (RSTP) FTP/HTTP/HTTPS	
Communication Service	Compliant reports Power quality summary Energy report EcoStruxure Power Events Analysis SMTP e-mail notification SNMP	
Tamperproof Of Settings	Protected by sealable cover	
Mounting Support	DIN rail	
Electrical Insulation Class	Class III conforming to EN/IEC 62052-11	
Isolation Voltage	III400690 V conforming to EN 61010-1:ed. 3 III347600 V conforming to UL 61010-1:ed. 3 III347600 V conforming to CSA C22.2 No 61010-1:ed. 3	
Width	160 mm	
Depth	135.3 mm	
Height	160 mm	
Net Weight	1.5 kg	

Environment

F14		
Electromagnetic Compatibility	EMC immunity conforming to IEC 62052-11	
	EMC immunity conforming to IEC 61326-1	
	EMC immunity conforming to IEC 61000-6-5	
	Electrostatic discharge immunity test conforming to IEC 61000-4-2	
	Immunity to radiated fields conforming to IEC 61000-4-3	
	Immunity to fast transients conforming to IEC 61000-4-4	
	Surge immunity test conforming to IEC 61000-4-5	
	Immunity to conducted disturbances conforming to IEC 61000-4-6	
	Immunity to magnetic fields at network frequency conforming to IEC 61000-4-8	
	Immunity to conducted disturbances - test level: 2150 kHz conforming to CLC/TR 50579	
	Voltage dips and interruptions immunity test conforming to IEC 61000-4-11	
	Immunity to impulse waves conforming to IEC 61000-4-12	
	Conducted and radiated emissions conforming to EN 55011	
	Conducted and radiated emissions class B conforming to EN 55032	
	Conducted and radiated emissions class B conforming to FCC part 15	
	Conducted and radiated emissions class B conforming to ICES-003	
	Surge withstand conforming to ANSI C37.90.1	
	Surge withstand conforming to IEEE C37.90.1	
p Degree Of Protection	IP65 front:	
. •	IP30 rear:	
Degree Of Protection	UL type 12, front	
Relative Humidity	595 %	
Ambient Air Temperature For Operation	-2570 °C	

Ambient Air Temperature For Storage	-4085 °C
Installation Category	III
Operating Altitude	03000 m
Standards	ANSI C12.20
	ANSI C37.90.1
	IEC 61000-4-15
	IEC 61000-4-30
	IEC 61010-1
	IEC 61326-1
	IEC 61557-12
	IEC 61850
	IEC 62052-11
	IEC 62052-31
	IEC 62053-22
	IEC 62053-23
	IEC 62053-24
	IEC 62586
	UL 61010-1
Quality Labels	ISO 9001
	ISO 14000

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	30.0 cm
Package 1 Width	30.0 cm
Package 1 Length	41.0 cm
Package 1 Weight	2.5 kg
Unit Type Of Package 2	S04
Number Of Units In Package 2	2
Package 2 Height	30.0 cm
Package 2 Width	40.0 cm
Package 2 Length	60.0 cm
Package 2 Weight	3.2 kg



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information