# **Product datasheet**





## Switch body, TeSys Control, 3 poles,25A

V0

#### Main

Range	TeSys
Product Name	TeSys VARIO
Device Short Name	V
Product Type	Switch body

### Complementary

Complementary	
Mounting Support	Symmetrical rail
	Plate
Performance Level	High performance
Number Of Poles	3P
Contact Type And Composition	3 NO
Network Type	AC
••	DC
Network Frequency	50/60 Hz
[Ue] lec Rated Operational Voltage	690 V AC 50/60 Hz
lec Rated Operational Power In W	11 kW at 500 V (AC-23A)
	11 kW at 690 V (AC-3)
	15 kW at 690 V (AC-23A)
	4 kW at 230240 V (AC-3)
	5.5 kW at 400415 V (AC-3)
	7.5 kW at 500 V (AC-3)
	5.5 kW at 230240 V (AC-23A)
	7.5 kW at 400415 V (AC-23A)
[le] Rated Operational Current	14.5 A AC-23 Ue: 400 V
[Ith] Conventional Free Air Thermal Current	25 A
[Ithe] Conventional Enclosed Thermal Current	20 A
Making Capacity ( I Rms)	250 A at 400 V AC-21A
	250 A at 400 V AC-22A
	250 A at 400 V AC-23A
Breaking Capacity	200 A at 400 V (AC-21A)
	200 A at 400 V (AC-22A)
	200 A at 400 V (AC-23A)
Rated Conditional Short Circuit	10 kA at 400 V - associated fuse 25 A aM
Current	10 kA at 400 V - associated fuse 25 A gG
[Icm] Rated Short Circuit Making Capacity	1 kA at 400 V at Ipeak
Intermittent Duty Class	30
Suitability For Isolation	Yes

Life Is On Schneider 25 Apr 2024



[Uimp] Rated Impulse Withstand Voltage	8 kV
[Icw] Rated Short-Time Withstand Rms Current	300 A at 400 V duration: 1 s
Mechanical Durability	100000 cycles
Electrical Durability	100000 cycles AC-21 30000 cycles DC-15
lec Terminal Connection	Power circuit: screw clamp terminals10 mm² - solid Power circuit: screw clamp terminals6 mm² - flexible - with cable end
Tightening Torque	Power circuit: 2.1 N.m - on screw clamp terminals
Height	74 mm
Width	55 mm
Depth	60 mm
Product Weight	0.2 kg

### **Environment**

Standards	IEC 60947-3
Product Certifications	UL CSA
	GL
	UKCA
	CCC
Degree Of Protection	IP20 conforming to IEC 60529
Protective Treatment	TC
Mechanical Robustness	Vibrations 10150 Hz (1 gn) conforming to IEC 60068-2-6 Shocks 11 ms (30 Gn) conforming to IEC 60068-2-27
Ambient Air Temperature For Operation	-2050 °C
Fire Resistance	960 °C conforming to IEC 60695-2-1

### **Packing Units**

r doming office	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	12 cm
Package 1 Width	8.4 cm
Package 1 Length	8.2 cm
Package 1 Weight	174 g
Unit Type Of Package 2	S03
Number Of Units In Package 2	24
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	4.668 kg
Unit Type Of Package 3	P06
Number Of Units In Package 3	192
Package 3 Height	77 cm
Package 3 Width	80 cm

Package 3 Length	60 cm
Package 3 Weight	45.844 kg

### **Contractual warranty**

Warranty 18 months

## Sustainability Green Premium

**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance

<b>⊘</b>	Toxic Heavy Metal Free
<b>⊘</b>	Mercury Free
<b>⊘</b>	Rohs Exemption Information Yes
<b>⊘</b>	Pvc Free
<b>⊘</b>	Halogen Free Product

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations