

Specifications

APC



InRow RC, 600mm, Chilled Water, 380-415V, 50/60Hz

ACRC602

Overview

Lead Time

Special Order - Call for Quoted Lead Times

Main

Main Input Voltage	400 V 3 phases
Input Connection Type	IEC 60309 16 A 3P + N + PE
Number Of Rack Unit	42U
Number Of Cables	2
Provided Equipment	Installation guide Operations and maintenance manual

General

Air Discharge Option	Horizontal
Intake Air Option	Rear return
Air Flow	2831.68 l/s
Minimum Water Inlet Temperature	7 °C
Condensate Pump Flow	0.03 m3/h

Physical

-	
Colour	Black
Height	199.1 cm
Width	60 cm
Depth	107 cm
Net Weight	345.45 kg
Mounting Preference	No preference
Mounting Mode	Not rack-mountable

Input

Network Frequency

50/60 Hz

Conformance

Product Certifications

cUL listed CE Industry Canada UL listed VDE

Communications & Management

Control Panel

Multifunction LCD status and control console

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	216.6 cm
Package 1 Width	113.7 cm
Package 1 Length	85 cm
Package 1 Weight	405.45 kg
Number Of Units In Package 3	1

Contractual warranty

Warranty

1 year (parts only), 1 year on-site repair or replace with factory authorized Start-Up

2

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Eu Rohs Directive

Under investigation