# **Product datasheet**





Actassi - cable - category 6A - FTP - 10G - 305m - blue - CM

ACTTG4P6ASCM3RBU

Discontinued on: Jun 15, 2023

#### Main

Range	Actassi
Product Or Component Type	Copper cable
Colour Tint	Blue
Cable Shielding Type	F/UTP

### Complementary

Type Of Cable	4 pair cables
Communication Network Category	6 <sub>A</sub>
Minimum Return Loss	Guaranteed: 20 dB at 1 kHz
	Guaranteed: 23 dB at 4 kHz
	Guaranteed: 24.5 dB at 8 kHz
	Guaranteed: 25 dB at 10 kHz
	Guaranteed: 25 dB at 16 kHz
	Guaranteed: 25 dB at 20 kHz
	Guaranteed: 24.3 dB at 25 kHz
	Guaranteed: 23.6 dB at 31.25 kHz
	Guaranteed: 21.5 dB at 62.5 kHz
	Guaranteed: 20.1 dB at 100 kHz
	Guaranteed: 18 dB at 200 kHz
	Guaranteed: 17.3 dB at 250 kHz
	Guaranteed: 16.8 dB at 300 kHz
	Guaranteed: 15.9 dB at 400 kHz
	Guaranteed: 15.2 dB at 500 kHz
Attenuation	Guaranteed: 2.1 dB @ 1 MHz per 100 m cable
	Guaranteed: 3.8 dB @ 4 MHz per 100 m cable
	Guaranteed: 5.3 dB @ 8 MHz per 100 m cable
	Guaranteed: 5.9 dB @ 10 MHz per 100 m cable
	Guaranteed: 7.5 dB @ 16 MHz per 100 m cable
	Guaranteed: 8.4 dB @ 20 MHz per 100 m cable

Guaranteed: 8.4 dB @ 20 MHz per 100 m cable Guaranteed: 9.4 dB @ 25 MHz per 100 m cable Guaranteed: 10.5 dB @ 31.25 MHz per 100 m cable Guaranteed: 15 dB @ 62.5 MHz per 100 m cable Guaranteed: 9.1 dB @ 100 MHz per 100 m cable Guaranteed: 27.6 dB @ 200 MHz per 100 m cable Guaranteed: 31.1 dB @ 250 MHz per 100 m cable Guaranteed: 34.3 dB @ 300 MHz per 100 m cable Guaranteed: 40.1 dB @ 400 MHz per 100 m cable

Guaranteed: 45.3 dB @ 500 MHz per 100 m cable

Power Sum Alien Near-End Crosstalk [Psanext]	67 dB at 1 MHz 67 dB at 4 MHz 67 dB at 8 MHz 67 dB at 10 MHz 67 dB at 10 MHz 67 dB at 20 MHz 67 dB at 20 MHz 67 dB at 31.25 MHz 67 dB at 31.25 MHz 65.6 dB at 62.5 MHz 65.6 dB at 100 MHz 58 dB at 200 MHz 55.3 dB at 300 MHz 53.5 dB at 400 MHz 53.5 dB at 500 MHz
Power Sum Attenuation To Alien Crosstalk Ratio Far-End [Psaacrf]	66.2 dB at 4 MHz 60.1 dB at 8 MHz 58.2 dB at 10 MHz 54.1 dB at 16 MHz 52.2 dB at 20 MHz 50.2 dB at 25 MHz 48.3 dB at 31.25 MHz 42.3 dB at 62.5 MHz 38.2 dB at 100 MHz 32.2 dB at 250 MHz 30.2 dB at 250 MHz 42.3 dB at 400 MHz 30.2 dB at 450 MHz 28.7 dB at 300 MHz 26.2 dB at 400 MHz 24.2 dB at 500 MHz
Near End Crosstalk [Next]	Guaranteed: 74.3 dB at 1 MHz Guaranteed: 65.3 dB at 4 MHz Guaranteed: 60.8 dB at 8 MHz Guaranteed: 59.3 dB at 10 MHz Guaranteed: 59.3 dB at 10 MHz Guaranteed: 56.2 dB at 16 MHz Guaranteed: 53.3 dB at 20 MHz Guaranteed: 53.3 dB at 25 MHz Guaranteed: 51.9 dB at 31.25 MHz Guaranteed: 47.4 dB at 62.5 MHz Guaranteed: 44.3 dB at 100 MHz Guaranteed: 39.8 dB at 200 MHz Guaranteed: 38.3 dB at 250 MHz Guaranteed: 37.1 dB at 300 MHz Guaranteed: 37.1 dB at 300 MHz Guaranteed: 33.8 dB at 400 MHz Guaranteed: 33.8 dB at 500 MHz
Input Impedance	100 Ohm (+/- 15 %) at 1100 MHz 100 Ohm (+/- 22 %) at 100250 MHz
Maximum Loop Resistance	72 Ohm
Capacitance Unbalance	330 pF / 100 m
Maximum Resistance Unbalance	5 %
Wire Insulation Material	PE
Conductor Material	Solid bare copper
Awg Gauge	AWG 23
Cable Outer Diameter	7.3 mm
Cable Length	305 m
Cable Weight	17 kg
Environment  Ambient Air Temperature For	75 °C
Operation Flame Retardance	CM
Standards	ISO/IEC 11801 Ea
	ANSI/TIA-568-C.2

# **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	24.0 cm
Package 1 Width	43.0 cm
Package 1 Length	43.5 cm
Package 1 Weight	19.4 kg

## **Contractual warranty**

Apr 25, 2024

Warranty 18 months

## Sustainability Green Premium\*

**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance



Reach Free Of Svhc



Rohs Exemption Information

Yes

### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
China Rohs Regulation	China RoHS declaration  Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations