Product datasheet

Specifications





TeSys GB2 - thermal-magnetic circuit breaker - 1P - 10 A - Id = 138 A

GB2CB16

Discontinued on: Aug 27, 2020

① Discontinued

Main

| mann | | |
|--|---|--|
| Range | TeSys | |
| Product Name | TeSys GB2 | |
| Device Short Name | GB2 | |
| Product Or Component Type | Circuit breaker | |
| Device Application | Control | |
| Poles Description | 1P | |
| Network Type | AC/DC | |
| Utilisation Category | Category A conforming to IEC 60947-2 DC-12 conforming to IEC 60947-5-1 DC-13 conforming to IEC 60947-5-1 | |
| Network Frequency | 50/60 Hz conforming to IEC 60947-2 | |
| Breaking Capacity | 2 kA lcu at 110 V AC 50/60 Hz conforming to IEC 60947-2 1.5 kA lcu at 230/240 V AC 50/60 Hz conforming to IEC 60947-2 1.5 kA lcu at 24 V DC conforming to IEC 60947-2 | |
| [Ics] Rated Service Short-Circuit Breaking Capacity | 75 % at 110 V AC 50/60 Hz conforming to IEC 60947-2 75 % at 230/240 V AC 50/60 Hz conforming to IEC 60947-2 | |
| Trip Unit Technology | chnology Thermal-magnetic | |
| Magnetic Tripping Current | 138 A | |

Complementary

| Mounting Mode | By clips |
|---|---|
| Mounting Support | Rail Plate |
| Mounting Position | Horizontal Vertical |
| Control Type | Toggle |
| [In] Rated Current | 10 A |
| [Ue] Rated Operational Voltage | 250 V AC 50/60 Hz conforming to IEC 60947-2 277 V AC 60 Hz conforming to CSA C22.2 No 235 277 V AC 60 Hz conforming to UL 1077 48 V DC |
| [Uimp] Rated Impulse Withstand Voltage | 4 kV conforming to IEC 60947-2 |
| Power Dissipation Per Pole | 2 W |
| Mechanical Durability | 8000 cycles |
| Electrical Durability | 8000 cycles |

| Connections - Terminals | Connector 1 cable(s) 0.756 mm ² solid without cable end Connector 2 cable(s) 0.754 mm ² solid without cable end Connector 1 cable(s) 0.754 mm ² flexible with cable end Connector 2 cable(s) 0.752.5 mm ² flexible with cable end | |
|-------------------------|--|--|
| Tightening Torque | 1.2 N.m on connector | |
| Mechanical Robustness | Shocks: 22 Gn for 20 ms conforming to IEC 60068-2-27 Vibrations: 5 Gn, 5110 Hz conforming to IEC 60068-2-6 | |
| Quantity Per Set | Set of 6 | |
| 9 Mm Pitches | es 2 | |
| Height | 74 mm | |
| Width | 15 mm | |
| Depth | 67 mm | |

Environment

| Standards | EN/IEC 60947-1 EN/IEC 60947-2 CSA C22.2 No 235 UL 1077 | |
|--|---|--|
| Product Certifications | UL CSA | |
| Protective Treatment | TC | |
| Ip Degree Of Protection | IP20 conforming to IEC 60529 | |
| Ambient Air Temperature For Operation | -2060 °C | |
| Ambient Air Temperature For Storage | rature For -4080 °C | |
| Fire Resistance | 960 °C conforming to IEC 60695-2-1 | |
| Operating Altitude | 3000 m | |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|-----------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 1.500 cm |
| Package 1 Width | 6.800 cm |
| Package 1 Length | 7.300 cm |
| Package 1 Weight | 52.000 g |
| Unit Type Of Package 2 | BB1 |
| Number Of Units In Package 2 | 6 |
| Package 2 Height | 9.500 cm |
| Package 2 Width | 10.000 cm |
| Package 2 Length | 10.000 cm |
| Package 2 Weight | 331.000 g |
| Unit Type Of Package 3 | S02 |
| Number Of Units In Package 3 | 72 |
| Package 3 Height | 15.000 cm |
| Package 3 Width | 30.000 cm |
| Package 3 Length | 40.000 cm |
| | |

Package 3 Weight

4.324 kg

Contractual warranty

Warranty

12 months

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc

| Toxic Heavy Metal Free | |
|----------------------------|-----|
| Mercury Free | |
| Rohs Exemption Information | Yes |

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|---|
| Eu Rohs Directive | Compliant EU RoHS Declaration |
| China Rohs Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure | Product Environmental Profile |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile | No need of specific recycling operations |