Product datasheet

Specifications





Feed unit for dry type transformers, Canalis KTA, aluminium, 3200A, 3L+N+PE, high lcw, made to measure, N1, RAL9001

KTA3200EL61

Main

Range	Canalis	
Product Name	КТ	
Product Or Component Type	Side feeder trunking	
Device Short Name	KTA	
Device Application	Feeder length	
Supply	Dry-type transformer	
Material	Aluminium	
[le] Rated Operational Current	3200 A at 35 °C	
Neutral Position	ition Right	
Earth Conductor	Standard earth	
Short-Circuit Level	cuit Level Reinforced version	
Provided Equipment	Trunking unit	

Complementary

Housing Material	Polyester film	
Contacts Material	Copper	
[Ue] Rated Operational Voltage	1000 V	
Network Frequency	50/60 Hz	
[Ui] Rated Insulation Voltage	1000 V	
[Icw] Rated Short-Time Withstand Current	113 kA	
[lpk] Rated Peak Withstand Current	248 kA	
Radiated Magnetic Field	2.1 μΤ	
Thermal Stress Limit	12769000 kA ² .s	
Thdi	015 % 3200 A 1533 % 4000 A	
Maximum Voltage Drop	<0.0018 V with power factor = 1 at 50 Hz with 1A for 100 m long <0.0019 V with power factor = 0.9 at 50 Hz with 1A for 100 m long <0.0018 V with power factor = 0.8 at 50 Hz with 1A for 100 m long <0.0017 V with power factor = 0.7 at 50 Hz with 1A for 100 m long	
Mounting Mode	By screws	
Mounting Support	Plate	
Polarity	3L + N + PE	

Number Of Tap-Off Outlets	0	
Standards	IEC 61439-1 IEC 61439-6	
Dimension Type	Made to measure	
Connection Pitch	470700 mm	
Bar Width	200 mm	
Depth	140 mm	
Height	324 mm	
Length	1900 mm	
Colour	White (RAL 9001)	
Linear Load	46 kg/m	

Environment

Ip Degree Of Protection		
Ik Degree Of Protection		
Derating Factor	035 °C (100 % of In) 3540 °C (97 % of In) 4045 °C (93 % of In) 4550 °C (90 % of In) 5055 °C (86 % of In)	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	50 cm
Package 1 Width	13.8 cm
Package 1 Length	190 cm
Package 1 Weight	55.75 kg



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

Ø	Reach Free Of Svhc	
Ø	Toxic Heavy Metal Free	
Ø	Mercury Free	
⊘	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information