# **Product datasheet**

Specifications





# trip unit MicroLogic 6.2 A for ComPact NSX 100/160/250 circuit breakers, electronic, rating 100A, 3 poles 3d

LV429110

(!) Discontinued

() Discontinued on: Mar 31, 2021

(!) End-of-service on: Mar 31, 2022

#### Main

IVIAIII	
Range	ComPact
Range Of Product	ComPact NSX100250
Product Or Component Type	Trip unit
Trip Unit Name	MicroLogic 6.2 A
Trip Unit Technology	Electronic
Range Compatibility	ComPact NSX100 ComPact NSX160 ComPact NSX250
Device Application	Distribution
Number Of Poles	3P
Protected Poles Description	3t
Trip Unit Protection Functions	LSIG
Protection Type	L : for overload protection (long time) S : for short time short-circuit protection I : for instantaneous short-circuit protection G : for ground fault protection
Trip Unit Rated Current	100 A at 40 °C
[Ue] Rated Operational Voltage	690 V AC 50/60 Hz
Network Type	AC
Network Frequency	50/60 Hz

### Complementary

Long-Time Pick-Up Adjustment Type Ir (Thermal Protection)	Adjustable 9 settings	
[Ir] Long-Time Protection Pick-Up Adjustment Range	40100 A	
Long-Time Protection Delay Adjustment Type Tr	Adjustable	
[Tr] Long-Time Protection Delay Adjustment Range	15…400 s at 1.5 x lr 0.35…11 s at 7.2 x lr 0.5…16 s at 6 x lr	
Thermal Memory	20 minutes before and after tripping	
Short-Time Protection Pick-Up Adjustment Type Isd	Adjustable 9 settings	
[Isd] Short-Time Protection Pick- Up Adjustment Range	1.510 x lr	

Short-Time Protection Delay Adjustment Type Tsd	Adjustable
[Tsd] Short-Time Protection Delay	00.4 s l²t=off
Adjustment Range	0.10.4 s l <sup>2</sup> t=on
Instantaneous Protection Pick-Up Adjustment Type Ii	Adjustable
[li] Instantaneous Protection Pick-	1.512 x In Compact NSX250
Up Adjustment Range	1.515 x In Compact NSX100
	1.515 x In Compact NSX160
Ground-Fault Protection Pick-Up Adjustment Type Ig	Adjustable
[Ig] Ground-Fault Protection Pick-	0.41 x ln for ln = 40 A
Up Adjustment Range	0.21 x In for In > 40 A
	lg enable on/off
Ground-Fault Protection Time Delay Adjustment Type Tg	Adjustable
[Tg] Ground-Fault Protection Time	00.4 s l <sup>2</sup> t=off
Delay Adjustment Range	0.10.4 s l <sup>2</sup> t=on
Earth-Leakage Protection	Without
Zone Selective Interlocking Zsi	With
Local Signalling	Flashing LED (green) for ready to operate
	LED 105 % Ir (red) for overload
	LED 90 % Ir (orange) for overload
Display Type	LCD display
Type Of Measurement	Ammeter
Communication Of Data	Maximeters/minimeters
	Instantaneous and demand values
	Power quality
	Demand current and power
	Protection and alarm settings
	Time-stamped histories and event tables
	Maintenance indicators
	Energy metering
Electrical Data Recording	Maintenance indicators

### Environment

Standards	EN/IEC 60947-2 UL 508
Product Certifications	EAC CCC Marine
Ambient Air Temperature For Operation	-2570 °C
Ambient Air Temperature For Storage	-4085 °C

# **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1

### **Contractual warranty**

Warranty

18 months

## Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



RoHS/REACh

### Well-being performance

Mercury Free

Rohs Exemption Information Yes

### **Certifications & Standards**

Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information