Specifications



() Discontinued

# trip unit TM16G, ComPact NSX 100, thermal magnetic, generator protection, 16 A rating, 3P 2d

LV429145

() Discontinued on: Jun 21, 2021

#### Main

| Range                          | ComPact  |
|--------------------------------|--|
| Range Of Product               | ComPact NSX100250  |
| Product Or Component Type      | Trip unit  |
| Trip Unit Name                 | TM-G   |
| Trip Unit Technology           | Thermal-magnetic   |
| Range Compatibility            | ComPact NSX100<br>ComPact NSX100 DC  |
| Device Application             | Generator  |
| Number Of Poles                | 3P   |
| Protected Poles Description    | 2t   |
| Trip Unit Protection Functions | LI   |
| Protection Type                | L : for overload protection (thermal)<br>I : for short-circuit protection (magnetic) |
| Trip Unit Rated Current        | 16 A at 40 °C  |
| [Ue] Rated Operational Voltage | 690 V AC 50/60 Hz<br>750 V DC  |
| Network Type                   | AC<br>DC   |
| Network Frequency              | 50/60 Hz   |

### Complementary

| Long-Time Pick-Up Adjustment<br>Type Ir (Thermal Protection) | Adjustable           |
|--|----------------------|
| [Ir] Long-Time Protection Pick-Up<br>Adjustment Range        | 0.71 x ln            |
| Long-Time Protection Delay<br>Adjustment Type Tr             | Fixed                |
| [Tr] Long-Time Protection Delay<br>Adjustment Range          | 120400 s at 1.5 x In |
| Short-Time Protection Pick-Up<br>Adjustment Type Isd         | Fixed                |
| [Isd] Short-Time Protection Pick-<br>Up Adjustment Range     | 63 A                 |
| Short-Time Protection Delay<br>Adjustment Type Tsd           | Fixed                |
| Earth-Leakage Protection                                     | Without              |

### Environment

| Standards                                | UL 508<br>EN/IEC 60947-2 |
|--|--------------------------|
| Product Certifications                   | CCC<br>Marine<br>EAC     |
| Ambient Air Temperature For<br>Operation | -2570 °C                 |
| Ambient Air Temperature For<br>Storage   | -5085 °C                 |

# **Packing Units**

| Unit Type Of Package 1       | PCE    |
|------------------------------|--------|
| Number Of Units In Package 1 | 1      |
| Package 1 Height             | 6.7 cm |
| Package 1 Width              | 9.7 cm |
| Package 1 Length             | 11 cm  |
| Package 1 Weight             | 353 g  |

### **Contractual warranty**

Warranty

18 months

### **Sustainability**

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

#### Well-being performance

| Mercury Free               |   |
|----------------------------|---|
| Rohs Exemption Information | Yes   |
| Eu Rohs Directive          | Compliant   |
|                            | EU RoHS Declaration   |
| China Rohs Regulation      | China RoHS declaration  |
|                            | Product out of China RoHS scope. Substance declaration for your information   |
| Weee                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |