Product datasheet

Specifications





Anti Harmonic detuned reactor 50kvar 190Hz (3.8) 7% 50Hz 400V

LVR07500A40T

Main

| Range | PowerLogic |
|---------------------------|----------------------------|
| Device Short Name | DR |
| Product Or Component Type | Detuned reactor |
| Network Frequency | 50 Hz |
| Reactive Power Rating | 50 kvar for 400 V AC 50 Hz |
| Network Rated Voltage | 400 V AC 50 Hz |
| Tuning Order | 3.8 - 190 Hz - 7 % - 50 Hz |

Complementary

| oompromontal y | |
|--|------------------------|
| Power Losses (Max) | 320 W |
| Value Of Inductance | 0.75 mH |
| Inductance Tolerance | - 5 % to 5 % per phase |
| Fundamental Current Rating | 72.2 A |
| Rms Current Rating | 77.9 A |
| Electrical Insulation Class | Class H |
| [Ui] Rated Insulation Voltage | 1.1 kV |
| Dielectric Test Voltage | 4 kV 50 Hz 1 minute |
| [Imp] Maximum Permanent Current | 1.2 x l1 |
| Harmonic Current Spectrum | 3.7 % x I3 |
| • | 38.2 % x I5 |
| | 13.6 % x I7 |
| | 4.9 % x l11 |
| Dynamic Withstand Current | 2.2 x lsc |
| [Ith] Conventional Free Air Thermal Current | 2 A at 250 V AC 50 Hz |
| Type Of Installation | Indoor installation |
| Type Of Cooling | Forced convection |
| Connections - Terminals | Pad terminal |
| Fixing Center | 200 x 125 mm |
| Height | 270 mm |
| Width | 260 mm |
| Depth | 200 mm |
| Net Weight | 22 kg |

Environment

| Standards | IEC 60068 | |
|--|--|--|
| Ip Degree Of Protection | IP00 | |
| Operating Altitude | <= 2000 m | |
| Ambient Air Temperature For Operation | 055 °C at <= 1000 m 050 °C at > 10002000 m | |
| Average Ambient Air Temperature For Operation | 50 °C at <= 1000 m (average over 24 hours) 40 °C at <= 1000 m (average over 1 year) 45 °C at > 10002000 m (average over 24 hours) 35 °C at > 10002000 m (average over 1 year) | |
| Climatic Withstand | Relative humidity: 2080 % Salt mist (400 V/50 Hz) : 250 hours | |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|----------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 53.0 cm |
| Package 1 Width | 40.0 cm |
| Package 1 Length | 60.0 cm |
| Package 1 Weight | 35.25 kg |
| Unit Type Of Package 2 | P06 |
| Number Of Units In Package 2 | 2 |
| Package 2 Height | 70.0 cm |
| Package 2 Width | 60.0 cm |
| Package 2 Length | 80.0 cm |
| Package 2 Weight | 75.5 kg |

Contractual warranty

Warranty

12 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc

Rohs Exemption Information Yes

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|---|
| Eu Rohs Directive | Compliant EU RoHS Declaration |
| China Rohs Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure | Product Environmental Profile |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile | No need of specific recycling operations |