# **Product datasheet**

Specification





Pendant control station, Harmony XAC, plastic, yellow, 6 push buttons with 1NO, 1 emergency stop NC

XACA6713

### Main

Range Of Product	Harmony XAC
Product Or Component Type	Pendant control station
Device Short Name	XACA

### Complementary

Complementary		
Control Station Type	Double insulated	
Enclosure Material	Polypropylene	
Electrical Circuit Type	Control circuit	
Enclosure Type	Complete ready for use	
Control Station Application	Control of single speed hoist motor	
Control Station Composition	6 push-buttons + 1 emergency stop	
Control Button Type	First push-button 1 NO raise, slow Second push-button 1 NO lower, slow Fourth push-button 1 NO left, slow Third push-button 1 NO right, slow Stop push-button Ø 40 mm 1 NC latching Fifth push-button 1 NO forward slow Sixth push-button 1 NO reverse, slow	
Product Compatibility	ZB2BE101 for each direction ZB2BE102 for emergency stop	
Mechanical Interlocking	With mechanical interlocking between pairs	
Control Station Colour	Yellow	
Connections - Terminals	Screw clamp terminals, 1 x 0.51 x 2.5 mm² without cable end Screw clamp terminals, 1 x 0.52 x 1.5 mm² with cable end	
Standards	IEC 60947-5-1 UL 508 CSA C22.2 No 14 IEC 60204-32	
Product Certifications	CCC GOST	
Protective Treatment	ТН	
Ambient Air Temperature For Operation	-2570 °C	
Ambient Air Temperature For Storage	-4070 °C	
Vibration Resistance	15 gn (f= 10500 Hz) conforming to IEC 60068-2-6	
Shock Resistance	100 gn conforming to IEC 60068-2-27	
Overvoltage Category	Class II conforming to IEC 61140	
Ip Degree Of Protection	IP65 conforming to IEC 60529	

Ik Degree Of Protection	IK08 conforming to IEC 62262	
Mechanical Durability	1000000 cycles	
Cable Entry	Rubber sleeve with stepped entry 826 mm	
Contact Code Designation	A600 AC-15, Ue = 240 V, Ie = 3 A conforming to IEC 60947-5-1 appendix A A600 AC-15, Ue = 600 V, Ie = 1.2 A conforming to IEC 60947-5-1 appendix A Q600 DC-13, Ue = 250 V, Ie = 0.27 A conforming to IEC 60947-5-1 appendix A Q600 DC-13, Ue = 600 V, Ie = 0.1 A conforming to IEC 60947-5-1 appendix A	
[Ithe] Conventional Enclosed Thermal Current	10 A	
[Ui] Rated Insulation Voltage	600 V (pollution degree 3)	
[Uimp] Rated Impulse Withstand Voltage	6 kV conforming to IEC 60947-1	
Contact Operation	Slow-break	
Maximum Resistance Across Terminals	25 MOhm	
Operating Force	10 N push-button 8 N emergency stop	
Short-Circuit Protection	10 A fuse protection by cartridge fuse type gG	
Rated Operational Power In W	40 W DC-13 for 1000000 cycles, operating rate <60 cyc/mn at 120 V, load factor = 0.5 (inductive load) conforming to IEC 60947-5-1 appendix C 48 W DC-13 for 1000000 cycles, operating rate <60 cyc/mn at 48 V, load factor = 0.5 (inductive load) conforming to IEC 60947-5-1 appendix C 65 W DC-13 for 1000000 cycles, operating rate <60 cyc/mn at 24 V, load factor = 0.5 (inductive load) conforming to IEC 60947-5-1 appendix C	
Terminals Description Iso N°1	(13-14)NO	
Terminals Description Iso N°2	(11-12)NC	
Terminal Identifier	nal Identifier (13-14)NO (11-12)NC	
Net Weight	0.845 kg	

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	10.000 cm
Package 1 Width	11.000 cm
Package 1 Length	70.000 cm
Package 1 Weight	1.141 kg
Unit Type Of Package 2	P06
Number Of Units In Package 2	25
Package 2 Height	75.000 cm
Package 2 Width	80.000 cm
Package 2 Length	60.000 cm
Package 2 Weight	36.525 kg

### **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance

<b>Ø</b>	Reach Free Of Svhc	
<b>Ø</b>	Toxic Heavy Metal Free	
<b>Ø</b>	Mercury Free	
<b>⊘</b>	Rohs Exemption Information	Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
<b>Environmental Disclosure</b>	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations