Product datasheet

Specifications





C60 - circuit breaker - C60H - 1P - 32A - C curve

25031

() Discontinued on: 5 Jul 2019

Main

| Mann | |
|---------------------------|---|
| Range Of Product | C60 |
| Range | Multi9 |
| Product Name | C60 |
| Product Or Component Type | Miniature circuit-breaker |
| Device Short Name | С60Н |
| Device Application | Distribution |
| Poles Description | 1P |
| Number Of Protected Poles | 1 |
| [In] Rated Current | 32 A at 30 °C |
| Network Type | AC DC |
| Trip Unit Technology | Thermal-magnetic |
| Curve Code | С |
| Breaking Capacity | 30 kA lcu at 130 V AC 50/60 Hz conforming to EN/IEC 60947-2 15 kA lcu at 230240 V AC 50/60 Hz conforming to EN/IEC 60947-2 20 kA lcu at 60 V DC 1P conforming to EN/IEC 60947-2 4 kA lcu at 400415 V AC 50/60 Hz conforming to EN/IEC 60947-2 10000 A lcn at 230/400 V AC 50/60 Hz conforming to EN 60898 |
| Suitability For Isolation | Yes conforming to IEC 60947-2 |

Complementary

| Network Frequency | 50/60 Hz |
|--|---|
| [Ue] Rated Operational Voltage | 230240 V AC 50/60 Hz 400415 V AC 50/60 Hz 130 V AC 50/60 Hz 230/400 V AC 50/60 Hz |
| Magnetic Tripping Limit | 510 x ln |
| [Ics] Rated Service Breaking Capacity | 7.5 kA conforming to EN/IEC 60947-2 - 230240 V AC 50/60 Hz 2 kA conforming to EN/IEC 60947-2 - 400415 V AC 50/60 Hz 25 kA conforming to EN/IEC 60947-2 - 130 V AC 50/60 Hz 7500 A conforming to EN 60898 - 230/400 V AC 50/60 Hz |
| Limitation Class | 3 conforming to EN/IEC 60947-2 |
| Contact Position Indicator | Yes |
| Control Type | Toggle |
| Local Signalling | ON/OFF indication |
| Mounting Mode | Clip-on |

| Mounting Support | 35 mm symmetrical DIN rail |
|---|---|
| Comb Busbar And Distribution Block Compatibility | NO |
| 9 Mm Pitches | 2 |
| Height | 81 mm |
| Width | 18 mm |
| Depth | 73 mm |
| Net Weight | 0.12 kg |
| Mechanical Durability | 20000 cycles |
| Connections - Terminals | Tunnel type terminals25 mm² flexible Tunnel type terminals35 mm² rigid |
| Tightening Torque | Power circuit: 3.5 N.m upside 3.5 N.m downside |
| Product Compatibility | C60 accessories C60 auxiliary |

Environment

| Standards | EN/IEC 60947-2 EN 60898 |
|--|-----------------------------|
| Tropicalisation | 2 conforming to IEC 60068-1 |
| Relative Humidity | 95 % at 55 °C |
| Operating Altitude | 2000 m |
| Ambient Air Temperature For Operation | -2560 °C |
| Ambient Air Temperature For Storage | -4070 °C |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|----------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 8.5 cm |
| Package 1 Width | 1.8 cm |
| Package 1 Length | 7.5 cm |
| Package 1 Weight | 0.115 kg |

Contractual warranty

Warranty

18 months

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



RoHS/REACh

Certifications & Standards

| Eu Rohs Directive | Compliant | |
|-------------------|---|--|
| | EU RoHS Declaration | |
| Weee | The product must be disposed on European Union markets following specific waste | |
| | collection and never end up in rubbish bins | |