Product datasheet

Specification





impulse relay iTL - 4P - 4 NO -16A - coil 12 VDC - 24 VAC 50/60Hz

A9C30114

! Discontinued on: 5 Aug 2021

(!) Discontinued

Main

Range Of Product	Acti9	
Product Name	Acti9 iTL	
Product Or Component Type	Impulse relay	
Device Short Name	iTL	
Device Application	Standard	
Poles	4P	
Pole Contact Composition	4 NO	
[In] Rated Current	16 A	
Network Type	AC	
[Uc] Control Circuit Voltage	24 V AC 50/60 Hz 12 V DC	

Complementary

Network Frequency	50/60 Hz	
[Ue] Rated Operational Voltage	415 V AC 50/60 Hz	
Control Type	Remote and manual control	
Control Signal Type	Impulse	
Switching Frequency	100 switching operations/day 5 switching operations/minute	
Impulse Duration	50 ms1 s	
Remote Control Type	Illuminated push-button 3 mA	
Local Signalling	ON/OFF indication	
Mounting Mode	Fixed	
Mounting Support	DIN rail	
9 Mm Pitches	4	
Height	84 mm	
Width	36 mm	
Depth	60 mm	
Electrical Durability	AC-21: 200000 cycles AC-22: 100000 cycles	

25 Apr 2024 Life Is On Schneider 1



Osmasskiens Terminals		
Connections - Terminals	Control circuit: tunnel type terminals 1 cable(s) 0.54 mm² rigid	
	Control circuit: tunnel type terminals 1 cable(s) 0.54 mm² rigid with cable end	
	Control circuit: tunnel type terminals 1 cable(s) 14 mm² flexible	
	Control circuit: tunnel type terminals 1 cable(s) 14 mm² flexible with ferrule	
	Power circuit: tunnel type terminals 1 cable(s) 1.54 mm² rigid	
	Power circuit: tunnel type terminals 1 cable(s) 1.54 mm² rigid with cable end	
	Power circuit: tunnel type terminals 1 cable(s) 1.54 mm² flexible	
	Power circuit: tunnel type terminals 1 cable(s) 1.54 mm² flexible with ferrule	
Wire Stripping Length	11 mm	
Tightening Torque	1 N.m	
Range Compatibility	Acti 9 iATEt	
	Acti 9 iATLc	
	Acti 9 iATLc+s	
	Acti 9 iATLm	
	Acti 9 iATLs	
	Acti 9 iETL iTL 16	

Environment

Standards	EN 669-1
	EN 669-2-2
Product Certifications	GOST
	CCC
Quality Labels	CEBEC
	IMQ
	NF
	KEMA
	VDE
	VDE
Noise Level	60 dB
Ip Degree Of Protection	IP20 conforming to IEC 60529 (on opening)
	IP40 conforming to IEC 60529 (in enclosure)
Pollution Degree	3
Tropicalisation	2
Relative Humidity	95 % at 55 °C
Ambient Air Temperature For Operation	-2050 °C
Ambient Air Temperature For Storage	-4070 °C

Packing Units

•		
Unit Type Of Package 1	PCE	
Number Of Units In Package 1	1	
Package 1 Height	7.000 cm	
Package 1 Width	3.600 cm	
Package 1 Length	9.500 cm	
Package 1 Weight	218.000 g	
Unit Type Of Package 2	BB1	
Number Of Units In Package 2	6	
Package 2 Height	8.500 cm	
Package 2 Width	9.200 cm	
Package 2 Length	22.200 cm	
Package 2 Weight	1.361 kg	
Unit Type Of Package 3	S03	

Number Of Units In Package 3	72
Package 3 Height	30.000 cm
Package 3 Width	30.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	16.790 kg

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

②	Mercury Free	
⊘	Rohs Exemption Information	Yes
⊘	Halogen Free Plastic Parts Product	

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations