

AS-Interface - for \emptyset 22 emergency stop - metal

ASISSLB4

- ! Discontinued on: 31 Dec 2015
- ! End-of-service on: 31 Dec 2020

(!) Discontinued

Main

Product Or Component Type	Interface for Ø 22 emergency stop
Range Compatibility	AS-Interface cabling system
Fixing Collar Material	Metal
As-Interface	0.B.F.F
Supply	Via AS-Interface

Complementary

Contacts Type And Composition	1 NC + 1 NC
Addressing	Using adjustment terminal
[Us] Rated Supply Voltage	24 V DC - 1515 %
Power Consumption In W	1.2 W
Current Consumption	45 mA for AS-Interface line
Connections - Terminals	AS-Interface line: IDC
Mechanical Durability	300000 cycles
Net Weight	0.08 kg

Environment

Standards	ISO 13849-1 category 4 EN/IEC 60947-5-1 EN/IEC 60204-1 EN 954-1 category 4
Product Certifications	TÜV UL CSA
Ip Degree Of Protection	IP20 conforming to IEC 60529
Ambient Air Temperature For Operation	-1055 °C
Ambient Air Temperature For Storage	-2585 °C
Shock Resistance	10 gn
Vibration Resistance	5 gn

Contractual warranty

Warranty 18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

trem being perfermence		
Mercury Free		
Rohs Exemption Information	Yes	
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	