

Limiter disconnector, TeSys Ultra, 32A, activation 50kA, 130kA at 440V, Direct mounting on power base

LUALB1

#### Main

Range	TeSys
Range Of Product	TeSys Ultra
Device Short Name	LUA
Product Or Component Type	Limiter disconnector
Product Compatibility	LUB LU2B

## Complementary

•	
[Ith] Conventional Free Air Thermal Current	32 A
Activation Threshold	50 kA
Breaking Capacity	70 kA at 690 V 130 kA at <= 440 V
[Ui] Rated Insulation Voltage	690 V conforming to EN 60947-1 690 V conforming to IEC 60947-1
Mounting Mode	Direct
Connections - Terminals	Connector 1 x 110 mm² flexible without cable end Connector 1 x 16 mm² flexible with cable end Connector 2 x 16 mm² flexible with cable end Connector 2 x 16 mm² flexible without cable end Connector 1 x 1.510 mm² solid Connector 2 x 1.56 mm² solid
Tightening Torque	1.92.5 N.m flat Ø 6 mm 1.92.5 N.m Philips No 2
Net Weight	0.31 kg

# **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	5.2 cm
Package 1 Width	11.0 cm
Package 1 Length	13.5 cm
Package 1 Weight	327.0 g

## Sustainability

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

## Well-being performance

<b>Ø</b>	Reach Free Of Svhc	
<b>②</b>	Toxic Heavy Metal Free	
<b>Ø</b>	Mercury Free	
	Rohs Exemption Information	Yes
Read	ch Regulation	REACh Declaration
Eu F	Rohs Directive	Compliant EU RoHS Declaration
Chin	na Rohs Regulation	China RoHS declaration
Wee	е	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins