Product datasheet





current transformer tropicalised DIN mount 600 5 for bars 10x40 20x32 25x25

METSECT5MC060

Main

Range	PowerLogic
Product Name	СТ
Product Or Component Type	Current transformer
Secondary Current	5 A
Accuracy Class	Class 0.5 at 12 VA Class 1 at 15 VA
[In] Rated Current	600 A

Complementary

Join promontary	
Current Transformer Type	Tropicalised for busbar and cable
Current Transformer Ratio	600/5
[Ith] Conventional Free Air Thermal Current	36 kA
Dynamic Withstand Current	2.5 lth
Maximum Safety Factor	5
[Ue] Rated Operational Voltage	< 720 V AC 50/60 Hz
[Ui] Rated Insulation Voltage	3 kV
Mounting Mode	By screws Clip-on Insulated locking screw
Mounting Support	DIN rail Mounting plate Busbar
Width	70 mm outside: 41 mm inner:
Height	95 mm outside: 41 mm inner:
Depth	45 mm frame: 65 mm total:
Diameter	32 mm
Net Weight	0.449 kg
[Uimp] Rated Impulse Withstand Voltage	3 kV
Electrical Insulation Class	Class B
Cable Outer Diameter	32 mm
Opening Of Bars	32.5 x 20.5 25.5 x 25.5 40.5 x 10.5

Sealing	Without
Environment	
Standards	VDE 0414 IEC 61869-2
Product Certifications	CE EAC
Ip Degree Of Protection	IP20
Relative Humidity	095 %
Ambient Air Temperature For Operation	-2560 °C
Packing Units	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	7.500 cm
Package 1 Width	9.100 cm
Package 1 Length	12.000 cm
Package 1 Weight	450 g

Unit Type Of Package 2

Package 2 Height

Package 2 Width

Package 2 Length

Package 2 Weight

Number Of Units In Package 2

S03

25

30.000 cm

30.000 cm

40.000 cm

11.691 kg



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
China Rohs Regulation	China RoHS declaration
Eu Rohs Directive	Compliant with Exemptions
Reach Regulation	REACh Declaration