Product datasheet

Specifications





servo motor MH3 070 2,2Nm,key,multi,brake,IP65/ IP67,6kRPM

MH30702P12F2200

Main

Range Compatibility	PacDrive 3
Product Or Component Type	AC servo motors
Device Short Name	MH3

Complementary

Compromontary	
Maximum Mechanical Speed	8000 rpm
[Us] Rated Supply Voltage	115480 V
Network Number Of Phases	Three phase
Continuous Stall Current	2.94 A
Continuous Stall Torque	2.48 N.m, 115480 V, three phase
Continuous Power	1380 W
Peak Stall Torque	7.4 N.m, 115480 V, three phase
Nominal Output Power	0.31 W, 115 V
	0.7 W, 230 V
	1.16 W, 400 V
	1.38 W, 480 V
Nominal Torque	2.37 N.m for LXM52 at 2.82 mA, 115 V, 1 phase
	2.23 N.m for LXM52 at 2.7 mA, 230 V, 1 phase
	2.01 N.m for LXM52 at 2.49 mA, 400 V, 3 phases
	1.89 N.m for LXM52 at 2.36 mA, 480 V, 3 phases
	2.37 N.m for LXM62 at 2.82 mA, 115 V, 1 phase
	2.23 N.m for LXM62 at 2.7 mA, 230 V, 1 phase
	2.01 N.m for LXM62 at 2.49 mA, 400 V, 3 phases
	1.89 N.m for LXM62 at 2.36 mA, 480 V, 3 phases
Nominal Speed	1250 rpm for LXM52 at 2.82 mA, 115 V, 1 phase
	3000 rpm for LXM52 at 2.7 mA, 230 V, 1 phase
	5500 rpm for LXM52 at 2.49 mA, 400 V, 3 phases
	7000 rpm for LXM52 at 2.36 mA, 480 V, 3 phases
	1250 rpm for LXM62 at 2.82 mA, 115 V, 1 phase
	3000 rpm for LXM62 at 2.7 mA, 230 V, 1 phase
	5500 rpm for LXM62 at 2.49 mA, 400 V, 3 phases
	7000 rpm for LXM62 at 2.36 mA, 480 V, 3 phases
Maximum Current Irms	9.68 A
Shaft End	Parallel key
Second Shaft	Without second shaft end
Shaft Diameter	11 mm
Shaft Length	23 mm
Key Width	4 mm
Ip Degree Of Protection	IP65 standard
Encoder Type	Multiturn SinCos Hiperface

Speed Feedback Resolution	128 periods
Holding Brake	With
Holding Torque	3 N.m
Mounting Support	International standard flange
Motor Flange Size	70 mm
Electrical Connection	Rotatable right-angled connectors
Torque Constant	0.84 N.m/A at 120 °C
Back Emf Constant	54.08 V/krpm
Number Of Motor Poles	10
Rotor Inertia	1.24 kg.cm ²
Stator Resistance	3.84 Ohm
Stator Inductance	12.19 mH
Stator Electrical Time Constant	3.2 ms
Maximum Radial Force Fr	710 N at 1000 rpm 560 N at 2000 rpm 490 N at 3000 rpm 450 N at 4000 rpm 410 N at 5000 rpm 390 N at 6000 rpm
Brake Pull-In Power	7 W
Type Of Cooling	Natural convection
Length	193 mm
Centring Collar Diameter	60 mm
Centring Collar Depth	2.5 mm
Number Of Mounting Holes	4
Mounting Holes Diameter	5.5 mm
Circle Diameter Of The Mounting Holes	82 mm
Net Weight	3.3 kg

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	11.5 cm
Package 1 Width	19.0 cm
Package 1 Length	39.5 cm
Package 1 Weight	2.3 kg

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Mercury Free
Rohs Exemption Information Yes
Pvc Free

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations