# **Product datasheet**

Specifications





## servo motor MH3 100 3,3Nm,key,single 16 lines,no brake,IP65/IP67,4kRPM

MH31001P16A2200

() Discontinued on: 9 Feb 2023

() Discontinued

#### Main

Range Compatibility	PacDrive 3	
Product Or Component Type	AC servo motors	
Device Short Name	MH3	

### Complementary

Complementary	
Maximum Mechanical Speed	6000 rpm
[Us] Rated Supply Voltage	115480 V
Network Number Of Phases	Three phase
Continuous Stall Current	3.15 A
Continuous Stall Torque	3.4 N.m, 115480 V, three phase
Continuous Power	1520 W
Peak Stall Torque	10.8 N.m, 115480 V, three phase
Nominal Output Power	0.35 W, 115 V
	0.67 W, 230 V
	1.26 W, 400 V
	1.52 W, 480 V
Nominal Torque	3.3 N.m for LXM52 at 3.07 mA, 115 V, 1 phase
	3.2 N.m for LXM52 at 2.99 mA, 230 V, 1 phase
	3 N.m for LXM52 at 2.83 mA, 400 V, 3 phases
	2.9 N.m for LXM52 at 2.75 mA, 480 V, 3 phases
	3.3 N.m for LXM62 at 3.07 mA, 115 V, 1 phase
	3.2 N.m for LXM62 at 2.99 mA, 230 V, 1 phase
	3 N.m for LXM62 at 2.83 mA, 400 V, 3 phases
	2.9 N.m for LXM62 at 2.75 mA, 480 V, 3 phases
Nominal Speed	1000 rpm for LXM52 at 3.07 mA, 115 V, 1 phase
	2000 rpm for LXM52 at 2.99 mA, 230 V, 1 phase
	4000 rpm for LXM52 at 2.83 mA, 400 V, 3 phases
	5000 rpm for LXM52 at 2.75 mA, 480 V, 3 phases
	1000 rpm for LXM62 at 3.07 mA, 115 V, 1 phase
	2000 rpm for LXM62 at 2.99 mA, 230 V, 1 phase
	4000 rpm for LXM62 at 2.83 mA, 400 V, 3 phases
	5000 rpm for LXM62 at 2.75 mA, 480 V, 3 phases
Maximum Current Irms	10.68 A
Shaft End	Parallel key
Second Shaft	Without second shaft end
Shaft Diameter	19 mm
Shaft Length	40 mm
Key Width	6 mm

IP65 standard
Single turn SinCos Hiperface
16 periods
Without
International standard flange
100 mm
Rotatable right-angled connectors
1.09 N.m/A at 120 °C
70.3 V/krpm
10
3.19 kg.cm <sup>2</sup>
4.12 Ohm
14.9 mH
4.5 ms
900 N at 1000 rpm 720 N at 2000 rpm 630 N at 3000 rpm 570 N at 4000 rpm 530 N at 5000 rpm
Natural convection
128.6 mm
95 mm
3.5 mm
4
9 mm
115 mm

### **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	21.0 cm
Package 1 Width	18.0 cm
Package 1 Length	35.6 cm
Package 1 Weight	4.04 kg

### Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

#### Well-being performance



#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	No need of specific recycling operations