Product datasheet

Specifications





Manual overload reset push button, Harmony XB4, black flush pushbutton Ø22 mm for 16...26 mm actuation distance

XB4BA822

() Discontinued

Discontinued on: 7 Aug 2023

Main

Range Of Product	Harmony XB4
Product Or Component Type	Manual overload reset push-button
Device Short Name	XB4
Bezel Material	Chromium plated metal
Fixing Collar Material	Zamak
Head Type	Standard
Mounting Diameter	22.5 mm
Operator Profile	Black flush, unmarked
Activating Distance	1626 mm

Complementary

Net Weight	0.038 kg
Resistance To High Pressure Washer	7000000 Pa at 55 °C, distance : 0.1 m
Shape Of Signaling Unit Head	Round
Operating Travel	10 mm
Mechanical Durability	5000000 cycles

Environment

Protective Treatment TH Ambient Air Temperature For Storage -4070 °C Ambient Air Temperature For Operation -4070 °C Electrical Shock Protection Class Class I conforming to IEC 60536 Ip Degree Of Protection IP66 conforming to IEC 60529 Nema Degree Of Protection NEMA 13 NEMA 4X Ik Degree Of Protection IK03 conforming to IEC 50102 Standards JIS C8201-5-1 IEC 60947-5-1 CSA C22.2 No 14 IEC 60947-5-1 UL 508 IEC 60947-5-5 JIS C8201-1		
Storage -4070 °C Operation -4070 °C Electrical Shock Protection Class Class I conforming to IEC 60536 Ip Degree Of Protection IP66 conforming to IEC 60529 Nema Degree Of Protection NEMA 13 NEMA 4X Ik Degree Of Protection IK03 conforming to IEC 50102 Standards JIS C8201-5-1 IEC 60947-5-1 CSA C22.2 No 14 IEC 60947-5-4 IEC 60947-5-4 IEC 60947-5-5	Protective Treatment	тн
Operation Electrical Shock Protection Class Class I conforming to IEC 60536 Ip Degree Of Protection IP66 conforming to IEC 60529 Nema Degree Of Protection NEMA 13 NEMA 4X Ik Degree Of Protection IK03 conforming to IEC 50102 Standards JIS C8201-5-1 IEC 60947-5-1 CSA C22.2 No 14 IEC 60947-5-4 IEC 60947-5-4 IEC 60947-5-5		-4070 °C
Ip Degree Of Protection IP66 conforming to IEC 60529 Nema Degree Of Protection NEMA 13 NEMA 4X Ik Degree Of Protection IK03 conforming to IEC 50102 Standards JIS C8201-5-1 IEC 60947-5-1 CSA C22.2 No 14 IEC 60947-5-4 IEC 60947-5-4 IEC 60947-5-5		-4070 °C
Nema Degree Of Protection NEMA 13 NEMA 4X Ik Degree Of Protection IK03 conforming to IEC 50102 Standards JIS C8201-5-1 IEC 60947-5-1 CSA C22.2 No 14 IEC 60947-5-4 IEC 60947-5-4 IEC 60947-5-4 IEC 60947-5-5	Electrical Shock Protection Class	Class I conforming to IEC 60536
NEMA 4X Ik Degree Of Protection IK03 conforming to IEC 50102 Standards JIS C8201-5-1 IEC 60947-5-1 CSA C22.2 No 14 IEC 60947-5-4 IEC 60947-5-4 IEC 60947-5-3 IEC 60947-5-5	Ip Degree Of Protection	IP66 conforming to IEC 60529
Standards JIS C8201-5-1 IEC 60947-5-1 CSA C22.2 No 14 IEC 60947-5-4 IEC 60947-1 UL 508 IEC 60947-5-5	Nema Degree Of Protection	
IEC 60947-5-1 CSA C22.2 No 14 IEC 60947-5-4 IEC 60947-1 UL 508 IEC 60947-5-5	Ik Degree Of Protection	IK03 conforming to IEC 50102
	Standards	IEC 60947-5-1 CSA C22.2 No 14 IEC 60947-5-4 IEC 60947-1 UL 508 IEC 60947-5-5

GL LROS (Lloyds register of shipping) CSA UL listed DNV BV

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	12.0 cm
Package 1 Width	3.5 cm
Package 1 Length	10.0 cm
Package 1 Weight	37.0 g

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes


Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information

Product datasheet

Dimensions Drawings

Dimensions



e: panel thickness: 1 to 6 mm / 0.04 to 0.24 in.

Product datasheet

Mounting and Clearance

Panel Cut-out for Pushbuttons, Switches and Pilot Lights (Finished Holes, Ready for Installation)

